

PRIMARY CORNER DESCRIPTION N 1/16 Secs. 27 & 28

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Douglas Co. Surveyors Office - George J. Wenderoth - 1947 -
C.S. File 40/29 & M4-75

Set - 1" I.P.
10" Fir N.21°37'E. 76.0
16" Fir N.74°53'W. 145.5

BLM Resurvey by Lynn M. Roseberry and Larry D. Evans,
Cadastral Surveyors, under Group #778, surveyed July/Sept.
1972- (DCSO records Vol. 38 Page(s) 15489)

The N 1/16 sec. cor. of secs. 27 & 28, established & recorded
by Wenderoth in 1947, monumented with an iron pipe, 1" dia.,
firmly set, protruding 4" above ground, from which BTs mkd.
by Wenderoth:
A Fir, 13" dia., bears N.20°E., 115 lks., with healed
double blaze.
A Fir, 28" dia., bears N.77°W., 222 lks., with healed
double blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap mkd:
N 1/16
S 28 | S 27
1972
From this point, a local corner, established by person(s)
unknown, bears N. 3 3/4°W., 57½ lks., monumented with an iron
bolt, 1" dia., with 1½" squared head, firmly set, protruding
9" above ground.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 4/5/2001 - C.S. File 66/21-5

Found - 1972 BLM brass cap protrudes 10" out of ground
(Note: accessible when lake is low) approx. 50
ft. from full pool shore.
13" now 16" dia., 30 ft. tall D.Fir snag with a
fully healed double blaze bears N.20°E., 75.9 ft.
28" now 33" dia., 6 ft. tall D.Fir stump with a
fully healed blaze, bears N.76¼°W., 146.5 ft.
(Rec. N.77°W., 146.5 ft.)
New - 16" dia., D.Fir double blazed & scribed "N 1/16 S28
CS BT" bears N.50°W., 90.2 ft.
7" dia., D.Fir double blazed & scribed "N 1/16 S27
CS BT" bears N.11½°E., 101.0 ft.
Note - Iron bolt not found.
Compass decl. 17 3/4°E.
See last Pg for pictures.

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 400260

PRIMARY CORNER DESCRIPTION N 1/16 Secs. 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

