

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7788)

Set post, cor. to secs. 21, 22, 27 and 28, from which
A Fir 10" dia., bears N.80°E., 39 lks. dist.
A Fir 10" dia., bears S.12°E., 38 lks. dist.
An Alder 6" dia., bears S.88°W., 12 lks. dist.
An Alder 5" dia., bears N.58°W., 13 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7826-27)

The Sec. cor., which is a post, greatly decayed with marks nearly obliterated, I find the 4 witness trees.
I remove this post and set a stone 16x10x10 ins., 12" in the ground, for corner, marked with 3 notches on E. and 2 notches on S. edges; from which
A Fir 10" dia., bears N.80°E., 39 lks. dist. mkd. T31S R4W S22 BT.
A Fir 10" dia., bears S.12°E., 38 lks. dist. mkd. T31S R4W S27 BT.
An Alder 6" dia., bears S.88°W., 12 lks. dist. mkd. T31S R4W S28 BT. This tree is dead. In its stead,
I mark a Fir 10" dia., which bears S.14¼°W., 31 lks. dist. T31S R4W S28 BT.
An Alder 5" dia., bears N.58°W., 13 lks. dist. mkd. T31S R4W S21 BT. This tree is dead. In its stead, I mark an Alder 10" dia., which bears N.24½°W., 53 lks. dist.

Douglas County Surveyors Office - George Wenderoth, Deputy - Dec. 1947 - C.S. File 40/29 & M4-75

Found - 20" Fir bearing S.14°30'W., 20.5 ft. dist.
Drove a 1¼" I.Pipe for the corner with BTs marked:
8" Yew bearing S.65°18'E., 45.9 ft. dist.
4" Hemlock bearing N.5°30'E., 53.5 ft. dist.
26" Fir bearing N.33°W., 60.1 ft. dist.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - March 1966 - C.S. File 54/20-24

Found - Iron pipe.
Orig. 20" Fir, now 21", S.14½°W., 20.5 ft., opened for scribe.
(Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

8" Yew wood, now 11", S.65°18'E., 45.9 ft. (dist. should be 47.0 ft.), scribing visible "S27 CS BT"
4" Hemlock now 12", N.5½°E., 53.6 ft.
26" Fir N.33°W., 60.1 ft., shows good scar.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 4 W
S 21 | S 22
S 28 | S 27
1966

(Brass cap set alongside iron pipe)
Reblazed and rescribed:
12" Hemlock N.5½°E., 53.5 ft. scribed T31S R4W S22 CS BT.
34" Fir N.33°W., 60.1 ft. scribed T31S R4W S21 CS BT
New BT - 9" Yewwood S.24°W., 44.1 ft. scribed T31S R4W S28 CS BT.

Cor. Fd. and used in BLM Resurvey by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #778, surveyed July/Sept. 1972- (DCSO records Vol. 38 Page(s) 15478-79)