

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7828)

Set a stone 16x10x6 ins., 12" in the ground for cor. to secs. 15, 16, 21 and 22, marked with 3 notches on E. and S. edges; from which

A Fir 14" dia., bears N.34½°E., 41 lks. dist. mkd. T31S R4W S15 BT.

A Fir 10" dia., bears S.8°E., 37 3/4 lks. dist. mkd. T31S R4W S22 BT.

A Fir 36" dia., bears S.57°W., 27½ lks. dist., mkd. T31S R4W S21 BT.

A Fir 36" dia., bears N.75°W., 112½ lks. dist. mkd. T31S R4W S16 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - April 1966 - C.S. File 54/20-41

Found - No trace of stone at corner.

36" now 46" D.Fir N.75°W., 73.9 ft. (should be 75.9 ft.) shows good scar.

36" now 47" D.Fir S.57°W., 18.1 ft., opened and scribing visible.

14" now 27" D.Fir N.34½°E., 27.1 ft. shows good scar

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 4 W

S 16 | S 15

S 21 | S 22

1966

Set corner by 3 bearings and 1 distance.

New BT- 40" D.Fir N.88°E. 18.0 ft scribed "T31S R4W S15 CSBT"

Fd. and Used in BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18146-47)

Mark Smalley - For: Roseburg Resources - 3/29/2000 - C.S. File 65/37-29

Found - 1966 DCSO IPBC leans north.

1893 52" Fir N.75°W., 73.9 fair-healed face. (Orig)

1893 Fir stump S.57°W., 18.1 (Orig.)

1893 32" Fir N.34½°E., 27.1 good healed face. (Orig)

1966 41" Fir N.88°E., 18.0 good healed face.

New BT - 15" Hemlock N.62°W., 29.2 scribed "S16 BT"

Found OK by Max Hull, Dec. 2003 - M143-48 cont. next pg

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent survey by Arthur R. Rambo, Cadastral Surveyor, under Group No. 2705, surveyed April 2013 - (DCSO records Vol. 58 Page 23071 & **Survey plat 2014-1**)

The cor, of secs. 15, 16, 21, & 22, perpetuated by Smalley, in 2000, monumented with an iron post, 1½" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd from which the remains of original bearing trees

A fir, 36" dia., bears N.34½°E., 24.1 ft., with a healed blaze.

A sawed fir stump, 46" dia., bears S.57°W., 18.2 ft., with no scribe marks visible on open blaze.

A sawed fir stump, 55" dia., bears N.75°W., 76.3 ft., with a healed blaze. (Record, 74.3 ft.)

and a bearing tree mkd, by Powell, in 1966

A fir, 46" dia., bears N.88°E., 17.8 ft., with a healed blaze.

and a bearing tree mkd, by Smalley

A sawed hemlock stump, 16" dia., bears N.61¼°W., 31.1 ft., with scribe marks S 16 BT with brass washer mkd. 2354 visible on partially healed blaze,

and new bearing trees

A fir, 10" dia., bears S.54¾°E., 14.2 ft., mkd. T31S R4W S22 BT

A fir, 7" dia. bears S.74°W., 10.2 ft. mkd T31S R4W S21 BT

A fir, 6" dia., bears N.70¾°W., 44.2 ft., mkd. X at breast height, and BT at base.