

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7830)

-----  
Set a stone 20x10x3 ins., 15" in the ground, for 1/4 sec. cor. marked 1/4 on W. face; from which  
A Maple 14" dia., bears S.29°E., 43 lks. dist. mkd. 1/4 S BT  
A Maple 11" dia., bears S.79 1/2°W., 40 lks. dist. mkd. 1/4 S BT.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18147)

-----  
Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 31 S R 4 W  
1/4  
S 16 S 15  
1985

from which

A Hemlock 12" dia., bears S.52 3/4°E., 34 lks. dist. mkd. 1/4 S15 BT.

A Hemlock 15" dia., bears N.52°W., 80 1/2 lks. dist. mkd. 1/4 S16 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Mark Smalley - For: Roseburg Resources - 3/29/2000 - C.S. File 65/37-27

-----  
Found - 1985 BLM IPBC firm in ground.  
1985 23" Hemlock N.52°W., 53.1 good-scribe visible.  
1985 12" Hemlock S.52 3/4°E., 22.4 good-scribe visible.  
New BTs- 2001 10" Hemlock S.87°E., 47.6 scribed "1/4 S BT"  
2001 18" Hemlock S.72°E., 56.7 scribed "1/4 S BT"