

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7832)

Set a stone 16x10x4 ins., 12" in the ground for 1/4 sec. cor. marked 1/4 on W. face; from which

A Laurel 10" dia., bears N.47 1/2°W., 27 lks. dist. mkd. 1/4 S BT.

A Laurel 11" dia., bears N.15 3/4°E., 40 lks. dist. mkd. 1/4 S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd; O.A. Keatley; J.L. Markham - Aug. 18, 1959 - C.S. File 42/391-29

Determined by O.B.T.s

18" Laurel bears N.16°E., 26.4 ft., found scribe.

9" Laurel bears N.47°W., 17.8 ft., I rescribed 1/4 S9 BT.

At corner point, found stone and SET 3/4" x 24" Iron pipe, from which

18" Laurel bears N.79°W., 36.0 ft. mkd. 1/4 S9 X BT.

14" Laurel bears N.15°W., 34.5 ft. mkd. 1/4 S9 BT.

12" Laurel bears N.76°E., 30.0ft. mkd. 1/4 S10 BT.

9" Laurel bears S.26°W., 8.0 ft. mkd. 1/4 S9 T31S R4W BT.

Douglas Co. Surveyors Office - M. Lenora Ladig; Gary L. Langlitz; James H. Cook, Crew - June 2, 1976 - C.S. File 59/15-11

Found - 3/4" x 18" Iron pipe, from which:

Orig. 11" now 22" Laurel bears N.16°E., 26.4 ft Tree has rotten insides, no trace of markings.

9" Laurel bears N.47°W., 17.8 ft., has faint scribing (tree appears to sprout from orig. NW. tree) Tree is alive.

18" Laurel bears N.79°W., 36.0 ft. Tree is alive with "1/4 S9 X" in unhealed blaze and "BT" bark scribe.

14" Laurel bears N.15°W., 34.5 ft. Tree is alive with partly healed blaze.

9" Laurel bears S.26°W., 9.0 ft. (call, S.26°W., 8.0 ft.) Tree is alive with "1/4 S9 T31S R4W BT" in visible bark scribe.

A downed Laurel with "1/4 S10 BT" in unhealed blaze (tree pushed up by cat)

At true corner point, set a 1" x 36" I.P. with brass cap marked: (Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas County Surveyor
T31S R4W
S 9 | S 10
¼ 1976
Placed found 3/4" I.P., south of cap.
New BT - 7" D.Fir bears N.45°W., 31.4 ft. scribed "¼ S9 CS
BT" in double scribe.
No suitable trees to the South.
Corner lies SW. from end of Rd. #31-4-3.0 on cutting line.

Fd. Ok by C Sweeden, July 2013 - M165-56