

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 34; and Sec. 4, T32-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 18 Page(s) 7784)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Laurel 10" dia., bears N.50°W., 9 lks. dist. A Fir 20" dia., bears South, 45 lks. dist.</p>
<p>GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8507-08)</p> <p>-----</p> <p>The ¼ sec. cor. post destroyed; bearing trees standing, from which I reestablish this ¼ sec. corner as follows: Set a Madrona post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. corner, marked ¼ S. on N. face, from which A Madrona 10" dia., bears N.50°W., 9 lks. dist. mkd. ¼ SBT. A Fir 20" dia., bears South, 45 lks. mkd. ¼ S BT.</p>
<p>GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12788)</p> <p>-----</p> <p>The ¼ sec. cor., determined at record bearing and distance from each of the original bearing trees: A Madrona 12" dia., bears N.50°W., 9 lks. dist., mkd. ¼ S on opened blaze. A Fir 44" dia., bears South, 45 lks. dist., marked ¼ S3 BT on opened blaze.</p> <p>At the corner point Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked</p> <p style="text-align: center;">T31S ¼ <u>S 34</u> S 3 T32S R4W 1959</p> <p>from which new bearing trees A Fir 22" dia., bears N.42°E., 37 lks. dist., mkd. ¼ S34 BT. A Fir 20" dia., bears S.25°E., 48 lks. dist., mkd. ¼ S3 BT.</p>
<p>Cor. Fd. and used in BLM resurvey by Roseberry and Evans, Group #778, surveyed July/Sept. 1972 (DCSO records, Vol. 38 Pages 15465-66)</p>
<p>Fd ok by Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/27/1998 - C.S. File 66/4-12</p>