

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 440140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Resurvey by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #778, surveyed July/Sept. 1972- (DCSO records Vol. 38 Page(s) 15504)

-----  
Point for the center ¼ sec. cor. of sec. 34, at intersection with the E. and W. center line of sec. 34.  
Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd: C ¼ S 34  
1972

from which

- A Hemlock 6" dia., bears N.84°E., 35 lks. dist. mkd. C¼ S34 BT.
- A Fir 12" dia., bears S.24°E., 39 lks. dist. mkd. C¼ S34 BT.

BLM Dependent resurvey by Ernest Q. Lundeen, Cadastral Surveyor, under Group No. 2828, surveyed April 2016 - (DCSO records Vol. 58 Page(s) 23492 & T31-4 Plat 2017-1)

-----  
The center ¼ sec. cor. of sec. 34, monumented with an iron post, 2½" dia., firmly set, projecting 6" above the ground with brass cap (properly) mkd.  
from which bearing trees mkd. by Roseberry and Evans in 1972  
A fir, 21" dia., bears S.26½°E., 25.2 ft., with a healed blaze. (Record, S.24°E., 25.7 ft.)  
A hemlock, 12" dia., bears N.83½°W., 23.1 ft., with a healed blaze. (Record, N.84°E.)