

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7831)

Set a stone 14x10x4 ins., 10" in the ground, for ¼ sec. cor. marked ¼ on N. face; from which

A Fir 17" dia., bears N.16 ¾°E., 40½ lks. dist. mkd. ¼ S BT.

A Fir 14" dia., bears S.82½°W., 43½ lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd; O.A. Keatley; J.L. Markham - Aug. 18, 1959 - C.S. File 42/391-35

Determined by O.B.Ts:

30" Fir bears N.17°E., 27.0 ft.

24" Fir bears S.82°W., 30.2 ft.

At corner point, SET stone and iron bolt ½" x 20", from which 20" Fir bears S.10°W., 60.0 ft. mkd. ¼ S15 BT.

8" Laurel bears N.55°W., 23.5 ft. mkd. ¼ S10 BT.

7" Laurel bears N.45°W., 40.6 ft. mkd. ¼ S10 T31S R4W BT.

5" Laurel bears N.9°E., 24.3 ft. mkd. ¼ S BT.

Top of ridge bears East 165.0 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Co. Surveyor - Stephen J. Flause - 7/31/2012 - C.S. File 67/36-20

Found - ½" iron bolt leaning westerly 2" below ground.
12"x10"x4" shale stone, no marks fd along westerly edge of bolt.

Orig. & 1959 distance measurements fd to be sloped.

7" now 30" dia., 2½ ft. high D.Fir stump with a fully healed single blaze, bears N.18½°E., 26.0 ft. (N.17°E., 27.0 ft.) OBT

14" now 24" dia., 2 ft high D.Fir stump with a fully healed double blaze, bears S.81°W., 26.6 ft. (S.82°W., 30.2 ft.) OBT

20" now 21" dia., 4 ft. high D.Fir stump with a rotted blaze, bears S.10°W., 59.2 ft. (S.10°W., 60.0 ft.) 1959

8" now 10" dia., 3 ft. high broken madrone stump with a rotted single blaze, bears N.51°W., 21.6 ft. (N.55°W., 23.5 ft.) 1959

7" now 12" dia., standing partially alive madrone with a rotted blaze, bears N.44°W., 37.2 ft. (N.45°W., 40.6 ft.) 1959

5" now young madrones growing from root crown. Fd. near record (N.9°E., 24.3 ft.) 1959 Cont.

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New - Set 2½" dia., brass cap on a 1½" by 32" long iron pipe is set at plumb position of fd 1959 bolt, protrudes 4" out of ground. 1959 bolt measured 18½" long is set along north edge of BC/IP, stone placed along westerly edge of BC/IP. BC mkd:

DOUGLAS COUNTY SURVEYORS

T31S

¼ $\frac{S\ 10\ R}{S\ 15\ 4}$

2012 W

OFFICE

15" dia., D.Fir double blazed & scribed "¼ S 15 CS BT" bears S.13°W., 13.6 ft.

8" dia., D.Fir double blazed & scribed "¼ S10 CS BT" bears N.21°W., 6.9 ft.

7" dia., D.Fir double blazed & scribed "¼ S15 CS BT" bears N.51°E., 8.5 ft.

7" dia., D.Fir double blazed & scribed "¼ S10 CS BT" bears S.54½°E., 29.5 ft.

Note - On steep SW'ly slope approx. 165 west of a ridge. Compass decl. 15½°E.

Fd. Ok by C Sweeden, July 2013 - M165-56