

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 444700

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 34, T30-4 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6986)

Set ¼ sec. post at proper distance; from which
A Laurel 6" dia., bears S.6°E., 80 lks.
A Chinquapin, 4" dia., bears N.45°E., 50 lks.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7019)

Set a Laurel post, 3 ft long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ on N face from which
A Fir, 42" dia., bears S.5°E., 4 lks., mkd: ¼ S BT.
A Cedar, 12" dia., bears N.27°E., 9 lks., mkd: ¼ S BT.

Bruce Shaner - For: Roseburg Resources Co. - July 2000 - C. S. File 65/30-190 & M 132-37

Set - 3/4"x40" iron rod with a 2½" alum. cap mkd:
ROSEBURG RESOURCES CO.
S ¼
S 34
RLS 430 2000
6" D.Fir BT, I scribed "S34 ¼ BT" bears N.1°W. 48.0 ft.
16" D.Fir BT I scribed "S34 ¼ BT" bears N.44°E. 16.3 ft.
18" D.Fir BT I scribed "S34 ¼ BT" bears N.1°E. 81.7 ft.
8" D.Fir BT I scribed "S34 ¼ BT" bears N.55°W. 36.5 ft.
6' steel post bears West 1.0 ft.