

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7786)

-----  
Set ¼ sec. post, top of spur, course E., from which  
A Laurel 5" dia., bears N.72°E., 43 lks. dist.  
A Fir 36" dia., bears S.55°W., 45 lks. dist.

Fd. and used in GLO resurvey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 - (DCSO records, Vol. 18 Page 7815)

BLM Resurvey by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #778, surveyed July/Sept. 1972- (DCSO records Vol. 38 Page(s) 15470)

-----  
Point for the ¼ sec. cor. of secs. 34 and 35, determined by the method of irregular boundaries: there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd: T 31 S R 4 W

¼  
S 34 | S 35  
1972

from which

A Fir 8" dia., bears N.55°E., 62½ lks. dist. mkd. ¼ S35 BT  
A Ponderosa Pine 18" dia., bears S.75°W., 197½ lks. dist. mkd. ¼ S34 BT.

BLM Dependent resurvey by Ernest Q. Lundeen, Cadastral Surveyor, under Group No. 2828, surveyed April 2016 - (DCSO records Vol. 58 Page(s) 23492 & T31-4 Plat 2017-1)

-----  
The ¼ sec. cor. of secs. 34 & 35, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground with brass cap (properly) mkd.

from which bearing trees mkd. by Roseberry and Evans in 1972

A fir, 19" dia., bears N.53½°E., 41.3 ft., with a healed blaze. (Record, N.55°E.)

A pine, 24" dia., bears S.75°W., 71.0 ft., with a healed blaze.

NAD 1983 (2011)

Latitude 42°50'03.31"N.

Longitude 123°09'02.47"W.