

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

From this point, a local corner established by Wenderoth, based on single proportionate method, bears S.50°18'W., 0.395 chs. dist., determined from the remains of bearing trees mkd. by Wenderoth:
A root hole bears N.61°43'W., 54 lks. dist. with a down Yew alongside, 10" dia., with scribe marks ¼ S CS BT visible on open double blaze.
This corner position was not accepted because it failed to protect the 1894 William Bushey record, which returned an irregular boundary.

Survey by Gregory Lang - For: Silver Butte Timber Co. - April 1995 (filed June 1996) - M 125-6

CORNER REPORT ONLY
Found - Brass cap at ¼ corner.
28½" Fir stump bears S.64 3/4°E., 97 lks.
Record 30" Fir, S.7¼°W., 134½ lks., is now down, uprooted, and cut off. Tag is still attached.

Fd OK by Kris DeGroot, 1/2006 - M 149-41

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff Lorsung - 5/30/2019 (filed 1/28/2021) - C.S. File 67/48-19

Found - A 2" I.D. iron pipe by Roseberry and Evans, in 1972, firmly set, projecting 5" above the ground with a 3¼" dia. brass cap (properly) marked
A B0 by Wenderoth in 1947 but not accepted as the ¼ Corner under a 1972 USBLM Dependent Resurvey -
A 1" I.D. iron pipe set bears S.50¼°W, 25.6 ft. (1972 USBLM Rec. S.50°18'W., 0.395 chs.) (the top of the pipe is bent Southwesterly)
A BT by Roseberry & Evans in 1972 -
A 14" dia. x 2' tall burned Fir stump bears S.64¾°E. 64.0 ft with clear evidence of healed blaze.
New BTs- A 17" dia. x 2' tall solid D.Fir stump bears S.84½°E., 18.9 ft to an 8" Mag Hub in the top center of the stump.
A 17"" dia. D.Fir bears S.9½°W., 53.5 ft, scribed "¼ S27", "CSBT" on a double blaze.
A 14" dia. maple bears N.1°W., 3 ft, scribed "¼ S27 CS", "BT" on a double blaze.

Continued next page

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - Compass declination $14\frac{1}{2}^{\circ}$ E.
The corner lies in mixed forest approximately 35 ft
West from the centerline of a gravel access road.
All BTs have BT Tags attached. All new BTs have
double blazed faces with bearing measured to the
center of the tree at the root crown and
distances measured to a 4" Mag Hub in the side
and center of the root crown.

Geodetic coordinates
Latitude: $43^{\circ}50'55.47''$ N. Longitude: $123^{\circ}09'03.61''$ W.
DATUM: NAD 83 SOURCE: GeoXT6000