

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7786)

Set post, cor. to secs. 22, 23, 26 and 27, from which
A Laurel 16" dia., bears N.30°E., 31 lks. dist.
A Fir 12" dia., bears S.50°E., 26 lks. dist.
A Chinquapin 5" dia., bears N.48°W., 25 lks. dist.
A Fir 24" dia., bears S.80°W., 19 lks. dist.

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7817)

The sec. cor., which is a post, 4" sq., firmly set, marked T31S S23 on NE.; R4W S26 on SE.; S27 on SW.; and S22 on NW. faces, with 2 notches on E. and S. edges, from which
A Laurel 16" dia., bears N.30°E., 31 lks. dist., mkd. T31S R4W S23 BT. This tree is dead. In its stead, I mark a Fir, 12" dia., which bears N.26½°E., 42½ lks. dist., T31S R4W S23 BT.
A Fir 12" dia., bears S.50°E., 26 lks. dist. mkd. T31S R4W S26 BT.
A Fir 24" dia., bears S.80°W., 19 lks. dist. mkd. T31S R4W S27 BT.
A Chinquapin 5" dia., bears N.48°W., 25 lks. dist., mkd. T31S R4W S22 BT.

Douglas Co. Surveyors Office - George Wenderoth, Deputy - Dec. 1947 - C.S. File 40/29; M 4-75

Found - 18" Fir bearing N.26°30'E., 28.0 ft. dist.
36" Fir bearing S.89°W., 12.5 ft. dist.
Drove a 1" I.Pipe for the corner and set the following BTs:
8" Fir bearing S.19°17'W., 24.2 ft. dist.
16" Fir bearing S.48°30'E., 14.5 ft. dist.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan/Feb. 1966 - C.S. File 54/20-12

Found - Iron rod at section corner.
8" Fir now dead, S.19°W., 24.2 ft., scribe visible "27 CS" (Dist. should be 32.0 ft.)
16" D.Fir now 18", S.48½°E., 14.5 ft., shows good scars.
(Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>Set Brass cap at cor. mkd: County Surveyors Office T 31 S R 4 W S 22 S 23 S 27 S 26 1966</p> <p>(Set brass cap alongside iron rod.) New BTs- 14" D.Fir S.78°E., 96.6 ft. scribed T31S R4W S CS BT 32" Fir stump N.67°W., 58.0 ft. scribed T31S R4W S CS BT.</p>
<p>Fd. and used in BLM Resurvey by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #778, surveyed July/Sept. 1972- (DCSO records Vol. 38 Page(s) 15472-73)</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/20/1998 - C.S. File 66/2-36</p> <p>-----</p> <p>Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 14" above ground, properly marked. 1966 6 sided threaded, probably gun barrel, that protrudes 24" above ground along SW'ly edge of BC/IP. 1947 16" now 31" dia., D.Fir with a fully healed double blazed S.48½°E., 14.5'. Agrees w/rec. 1947 14" now 23" dia., D.Fir with a fully healed double blaze bears S.78°E., 95.4' (Rec. S.78°E., 96.6' dist.)</p> <p>New BTs- 11" dia., D.Fir, double blazed & scribed "T31S R4W S27 CS BT" bears S.80½°W., 11.2'. 6" dia., D.Fir, double blazed & scribed "T31S R4W S23 CS BT" bears N.45°E., 8.9'.</p>
<p>Fd OK by Kris DeGroot, 1/2006 - M 149-41</p>
<p> </p>