

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7819)

-----  
Set a stone 16x10x6 ins., 12" in the ground, for cor. to secs. 14, 15, 22 and 23, marked with 2 notches on E. and 3 notches on S. edges; from which

A Chinquapin 8" dia., bears N.67¼°E., 89 lks. dist. mkd. T31S R4W S14 BT.

A Fir 16" dia., bears S.32°E., 27 lks. dist., mkd. T31S R4W S23 BT.

A Fir 3" dia., bears S.22¼°W., 13 lks. dist. mkd. T31S R4W S22 BT.

A Fir 20" dia., bears N.49¼°W., 32 lks. dist. mkd. T31S R4W S15 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Nov. 1959 - C.S. File 42/391-49

-----  
Determined by O.B.T.s:

40" Fir N.49°W., 21.2 ft., I rescribed S15 X BT.

24" Fir S.32°E., 17.8 ft.

At corner point, SET 2" x 36" Iron pipe, from which

6" Hemlock bears S.35°W., 22.8 ft. mkd. S23 R4W BT.

8" Maple S.10°W., 22.8 ft. mkd. S22 X BT.

8" Cedar S.11°E., 43.5 ft. mkd. S23 R4W BT.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18145-46)

-----  
The sec. cor., perpetuated and recorded by Markham in 1959, monumented with an iron pipe, 2" dia., firmly set, projecting 13" above ground, from which the original bearing trees:

A Fir 30" dia., bears S.32°E., 27 lks. dist., with healed blaze.

A Fir 44" dia., bears N.49¼°W., 32 lks. dist., with healed blaze.

and bearing trees mkd. by Markham:

A Cedar 15" dia., bears S.11°E., 65½ lks. dist., with healed blaze.

A Maple 13" dia., bears S.10°W., 34 lks. dist., with healed blaze.

A Hemlock 13" dia., bears S.35°W., 34 lks. dist., with healed blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: (Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>T 31 S R 4 W S 15   S 14 S 22   S 23 1985</p>
<p>Deposit iron pipe alongside and a white "DEEP-1" magnetic marker at base of stainless steel post.</p>
<p>Found OK by Max Hull, Dec. 2003 - M143-48</p>
<p>BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Technician under Group No. 2300 surveyed Dec 2004/Jan 2005 - (DCS0 recs Vol 56 Pg 21976)</p> <p>-----</p> <p>The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees A fir snag, 28" dia., 7 ft. high, bears S.32°E., 17.8 ft., with a healed blaze. A fir, 49" dia., bears N.49¼°W., 21.1 ft., with a healed blaze and X mkd. in the bark. and bearing trees mkd. by Markham, in 1959 A tin-capped cedar stump, 16" dia., bears S.11°E., 43.2 ft., with no marks visible. A maple, 16" dia bears S.10°W. 22.5 ft with a healed blaze A hemlock, 17" dia., bears S.35°W., 22.6 ft., with a healed blaze. and new bearing trees A fir, 14" dia., bears N.29°E., 16.2 ft., mkd. T31S R4W S14 BT. A fir, 10" dia., bears S.61¾°E., 33.8 ft., mkd. T31S R4W S23 BT.</p> <p>The geographic position (NAD 1983) of this cor. as determined by a differentially corrected, C/A code GPS observation, is as follows: Latitude: 42°52'14.7"N., Longitude: 123°09'02.2"W.</p>
<p>Fd. to be Ok, July 2012, R. Quimby - C.S. file 65/77-15</p>
<p style="text-align: right;">2</p>