

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7821)

Set a stone 10x8x7 ins., 7" in the ground, for ¼ sec. cor. mkd. ¼ on W. face; from which
A Laurel 10" dia., bears N.32°E., 30 lks. dist. mkd. ¼ S BT.
A Fir 14" dia., bears S.34°W., 48½ lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - March 1959 - C.S. File 42/391-17

Determined by O.B.Ts:
15" Fir bears S.34°E., 32.0 ft.
At corner point, found stone and SET 3/4" x 30" Iron pipe, from which
13" Laurel bears N.22°E., 20.0 ft. mkd. ¼ S14 BT.
16" Cedar bears N.48°W., 41.5 ft. mkd. ¼ S15 X BT.
50" Fir bears S.6°W., 39.0 ft. bark scribe ¼ S15 BT.

Ron Quimby - 7/2012 - C.S. File 65/77-10

Found - 3/4" I.Pipe by Markham
A 30" cedar N.48°W., 41.5 ft. good scar.
A down 50" Fir with scar.
New - A 13" D.Fir N.62°E., 17.5 ft. scribed ¼ S14 BT.