

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec Cor for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7821)

Set a stone 16x10x4 ins., 12" in the ground, for cor. to secs. 10, 11, 14 and 15, marked with 2 notches on E. and 4 notches on S. edges; from which

A Fir 16" dia., bears N.29°E., 22½ lks. dist. mkd. T31S R4W S11 BT.

A Fir 18" dia., bears S.22½°E., 22 lks. dist. mkd. T31S R4W S14 BT.

A Fir 18" dia., bears S.48°W., 59 lks. dist. mkd. T31S R4W S15 BT.

A Yew 10" dia., bears N.35¼°W., 8 lks. dist. mkd. T31S R4W S10 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Mar. 1959 - C.S. File 42/391-16

Determined by O.B.Ts:

30" Fir bears S.22°E., 18.0 ft.

28" Fir bears S.48°W., 42.6 ft.

At corner point, found stone and SET 3/4" x 30" Iron pipe, from which:

16" Yew bears S.57°W., 42.5 ft. mkd. S15 BT.

16" Fir bears S.72°W., 39.5 ft. mkd. S15 BT.

8" Yew bears East, 40.3 ft. mkd. S14 BT.

26" Fir bears N.74°E., 38.0 ft. mkd. X S11 X BT.

Creek bears East, 115.0 ft. dist.

Creek bears North, 56.0 ft. dist.

Fd ok by Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/27/1998 - C.S. File 66/4-12

Ron Quimby - 2/2012 - C.S. File 65/77-12

Found - 36" D.Fir S.48°W., 42.6 ft. good scar.

16" Yew S.57°W., 42.5 ft. good scar.

36" D.Fir S.22°E., 18.0 ft. good scar.

New - 5/8" I.Rod with 2½" alum cap marked Roseburg Resources Co.

A 10" D.Fir bears N.14°W., 10.2 ft. scribed T31 R04 S10 BT.

A 12" D.Fir bears N.82°E., 15.6 ft. scribed T31 R04 S11 BT.

continued next page

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec Cor for 10, 11, 14 and 15

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Carl Sweeden - For: Rome Creek Timber - July 2013 - M165-56

Found - 2½" ROSEBURG RESOURCES CO. ALUM CAP
12" D.Fir BT, N.82°E., 15.6' scribed vis., tag
37" D.Fir BT, N.74°E., 38.0' scar high up
8" Yew BT, East 38.0' to apparent root hole this
tree found with Markham 1x4x18 wood tag
36" D.Fir BT, S.10°E., 19.3', scar vis., tag
36" D.Fir BT stump, S.48°E., 40.2' (42.6') opened,
scribe vis.
18" Yew BT, S.57°W., 42.5' scribed vis., rotted
center, split butt
10" Hemlock BT N.22°W., 10.2' scribed vis. tag