

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7823)

Set a stone 14x10x6 ins., 10" in the ground, for ¼ sec. cor. marked ¼ on W. face; from which

A Fir 18" dia., bears S.47½°W., 23½ lks. dist. mkd. ¼ S BT.

A Fir 10" dia., bears N.8°E., 22 lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Feb/March 1959 - C.S. File 42/391-15

Determined by O.B.Ts:

12" Fir snag bears N.18°E., 14.5 ft., found scribe.

30" Fir snag bears S.47°W., 15.5 ft.

At corner point, SET ¾" x 30" Iron pipe, from which

7" Laurel bears S.26°W., 32.0 ft. mkd. ¼ S10 X X BT.

6" Laurel bears S.41°E., 33.2 ft. mkd. ¼ S11 T31S R4W BT.

6" Laurel bears N.66°W., 32.0 ft. mkd. ¼ S11 X BT.

Corner lies on very steep West face or rock slide in old burn.

Carl Sweeden - For: Rome Creek Timber - July 2013 - M165-56

Found - ¾" iron pipe up 0.60' now in stone collar
Orig. 10" fir BT down, N.18°E., 14.5', fd scribing.
Orig. 30" fir BT stump, S.47°W., 15.5', remains at ground level.

11" madrone BT, N.66°W., 32.0' scar vis.

10" madrone BT, S.41°E., 32,8' healed, tag

13" madrone BT, S.26°W., 27.85'

Set - 14" D.Fir BT, N.14°E 26.8' scribed "W ¼ S11 BT", tag