

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7824)

Set a stone 14x10x4 ins., 10" in the ground, for ¼ sec. cor. marked ¼ on W. face; from which

A Live Oak 8" dia., bears N.24½°E., 31 lks. dist., mkd. ¼ S BT.

A Live Oak 6" dia., bears N.6°W., 33 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - James W. Byron, Surveyor
John Powell, and crew - C.S. File 54/20-37A - Feb. 1966

Corner searched for, not found.

Carl Sweeden - For: Rome Creek Timber - Aug. 2013 - M165-61

Set - 5/8"x30" iron rod w/2½" Roseburg Resources Co. alum cap
mkd "T31S R4W ¼ RM S2|S3 LS 2752 2013" from which:

7.5" Live Oak BT, N.63°W., 14.85' scribed "T31S R4W E ¼ RM S3 BT"

9.5" W.Oak BT, N.26°W., 12.27' scribed "T31S R4W W E ¼ RM S3 BT"

14" Madrone BT, N.34½°E., 75.0' scribed "T31S R4W W ¼ RM S2 BT"

Set Mag nail w/washer on rock face N.87°E., 5.72' bears N.0°48'52"E., 22.99' from true point

Note- True position falls on rock face unable to set.