

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION C C for Secs. 2 and 3 only, N. Bdy

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7825)

-----  
At 3.00 chs. W. of the C C to secs. 34 and 35, Set a stone, 12x10x8 ins., 8" in the ground for closing cor. to secs. 2 and 3, marked C C on S. face, with 2 notches on E. and 4 notches on W. faces; from which

A Laurel 14" dia., bears S.36°E., 42½ lks. dist. mkd. T31S R4W S2 BT.

A Fir 20" dia., bears S.24°W., 67 lks. dist. mkd. T31S R4W S3 BT.

A Cedar 42" dia., bears N.46 3/4°E., 34½ lks. dist. mkd. T31S R4W C C S2 and 3 BT.

Survey by John H. Markham, Jr. - Wit: R.G. Boyd - For: Stomar Lumber Co. - Feb/Mar. 1959 - C.S. File 42/391-11

-----  
Determined by O.B.Ts.

48" Cedar uproot, bears N.47°E., 22.4 ft.

18" Laurel snag bears S.36°E., 27.7 ft.

26" Fir bears S.14°W., 44.2 ft., found scribe.

At corner point, Found stone and set 3/4" x 30" Iron rod, from which

9" Laurel bears N.50°E., 43.0 ft. mkd. S34 T30S R4W BT.

7" Laurel bears N.64°E., 38.4 ft. mkd. S34 R4W BT.

7" Chinquapin bears S.63°E., 43.5 ft. mkd. S2 X BT.

14" Chinquapin bears S.73°W., 37.5 ft. mkd. S3 T31S BT.

Sec. cor. for 34 and 35 bears East 198.0 ft.

Douglas Co. Surveyors Office - John Powell, Frank Jones and J. Brady, crew - Feb. 1966 - C.S. File 54/20-1

-----  
Found - Iron rod at corner.

Orig. 20" Fir now 25", S.14°W., 44.2 ft., shows scar

9" Laurel, now down, N.50°E., 43.0 ft.

7" Laurel now 9", N.64°E., 38.4 ft., bark scribed.

7" Chinquapin, now down, S.63°E., 43.5 ft.

14" Chinquapin now 16", S.73°W., 37.5 ft., scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office

R4W  $\frac{S \ 34}{S \ 3 \ S \ 2}$  T30S  
1966 T31S

(Set alongside iron rod)

Rescribed - 9" Laurel N.64°E., 38.4 ft. scribed "T30S R4W S34 CS BT"

continued next page

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION C C for Secs. 2 and 3 only, N. Bdy

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

David Edwards - For: Rome Creek Timber LLC - Sept. 2011 - M162-72

-----  
Found - 24" fir capped stump S.14°W., 44.2'  
11" madrone stump N.64°E., 38.4'  
16" chinquapin in poor cond. S.73°W., 3.5'  
New BTs- 10" dia. fir brs. S.70°E., 9.3'  
7" dia. fir brs. S.65W., 10.5'  
Both scribed as per 2009 manual.  
Set 6' steel post 2' east.

Fd. BC & 5 BTs by Carl Sweeden, 8/2013 - M165-61