

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 503700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, T30-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Page(s) 7111)

-----  
At point of intersection, Set a Fir post, 4 ft. long, 4" sq., 24" in the ground for closing corner to secs. 34 and 35, marked CC T30S R4W on N.; S35 on E.; and S34 on W. faces, from which

A Chinquapin 14" dia., bears N.15°E., 48½ lks. dist. mkd. T30S R4W S35 BT.

A Laurel 30" dia., bears N.29¼°W., 41 lks. dist., mkd. T30S R4W S34 BT.

A Fir 11" dia., bears S.6°W., 32 3/4 lks. dist., mkd. T30S R4W CC S34 and 35 BT.

Survey by John H. Markham, Jr. - Wit: R.G. Boyd - For: Stomar Lumber Co. - Feb. 1959 - C.S. File 42/356-8

-----  
At a point 198.0 ft. East of NW. corner Sec. 2, I Set 3/4" x 30" Iron pipe from S.C., from which

8" Laurel bears S.60°E., 27.5 ft. mkd. S2 T31S R4W BT.

30" Cedar bears S.40°W., 18.5 ft. mkd. S2 X BT.

6" Laurel bears N.77°W., 19.0 ft. mkd. S34 BT.

5" Fir bears N.18°E., 13.8ft. mkd. S35 BT.

Douglas Co. Surveyors Office - John Powell, Frank Jones and J. Brady, crew - Feb. 1966 - C.S. File 54/20-2

-----  
Found - Iron pipe.

7" Fir N.21°E., 13.7 ft., shows good scar.

27" Cedar S.40°W., 18.4 ft., scribe visible "S2".

9" Laurel S.61°E., 28.2 ft., bark scribed "S2 R31S R4W BT"

Set Brass cap at cor. mkd:

County Surveyors Office

T 30 S R4W S 34 | S 35

T 31 S S 2

1966

Set brass cap alongside iron pipe.

Rescribed - 9" Laurel S.61°E., 28.2 ft. "T31S R4W S2 CS BT".

Brass cap Fd. in BLM Admin. survey Aug. 1981 - See Roseburg BLM district office)

Bruce Shaner - For: Roseburg Resources Co. - July 2000 - C. S. File 65/30-19R & M132-37

-----  
Found - 2½" brass cap on a 1"x30" iron pipe, from which

20" D.Fir BT, face overgrown, bears N.21°E. 13.7 ft.

36" Cedar BT, now stump, bears S.40°W., 18.4 ft.

continued next page

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 503700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, T30-4

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New -	9" Madrone BT, bearing S.61°E., 28.2 ft., now down & dead. Iron pipe, 3/4"x30" alongside corner. 24" D.Fir BT, I scribed "T30S R4W S34 CC BT" bears N.26°W., 22.7 ft. 6 ft. steel fence post, bears North 1.0 ft.
David Edwards - For: Rome Creek Timber LLC - Sept. 2011 - M162-72 ----- Found as per C. S File 65/30-19R Set 6' steel post 2' East	