

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; and 2, T32-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 18 Page(s) 7784)

Set ¼ sec. post, from which
A Laurel 5" dia., bears N.5°E., 21 lks. dist.
A Laurel 5" dia., bears S.6°E., 13 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7813-14)

The ¼ sec. cor. is gone. I find 1 Laurel witness tree which is dead.
At cor. point, I set a stone 14x14x10 ins., 10" in the ground for ¼ sec. cor., marked ¼ on N. face; from which
A Laurel 5" dia., (6" now) bears N.5°E., 21 lks. mkd. ¼ S BT.
This is the original witness tree. I mark two new trees as follows:
A Laurel 4" dia., bears S.14°E., 20 lks. dist., mkd. ¼ S BT.
A Laurel 8" dia., bears N.67 ¾°W., 12 lks. dist., mkd. ¼ S BT.

Douglas County Surveyors Office - James W. Byron, Surveyor John Powell, and crew - C.S. File 54/20-6A

Corner searched for, not found.

Donald Martin - June 1970 - M41-5

Set - 5/8" iron rod & BTs

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/20/1998 - C.S. File 66/2-37

Found - 5/8" iron rod protrudes 3" above ground. M41-5
8" dia., Madrone with a partially healed single blaze scribing visible "S¼ S1 35 T" bears N.68°W. 19.5' (Agrees w/BT tag dated 5/70 by Martin) M41-5
16" dia., Madrone with a partially healed single blaze, scribing visible "N ¼ S2 BT" bears S.44½°W., 33.7' (Rec. per BT Tags S.40¼°W., 33.7', dated 5/70 by DRM) M41-5

(Cont. next page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35; & 2, T32-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BTs- 18" dia. D.Fir, double blazed & scribed "¼ S2 CS BT"
bears S.73°W., 7.1'.
15" dia., D.Fir, double blazed & scribed "¼ S35 CS
BT" bears N.14°E., 23.6'
New Blaze lines run south & east from fd. IR.

Fd. Ok by K. DeGroot 3/2008 - M146-71
Fd 5/8" IR by M Heimburger, 11/2018 M175-16