

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7816)

Set a stone 14x8x6 ins., 10" in the ground, for ¼ sec. cor. mkd. ¼ on N. face; from which

 A Fir 12" dia., bears S.84°W., 59 lks. dist. mkd. ¼ S BT.

 A Laurel 3" dia., bears N.81 3/4°E., 5¼ lks. dist. mkd. ¼ S BT.

BLM remonumentation by Lynn M. Roseberry, Cadastral Surveyor, under Group #1000, surveyed Aug. 1980 - (DCSO records Vol. 45 Page(s) 17450)

The ¼ sec.cor., monumented with the original basalt stone, 14 x 8 x 6 ins., loosely set in a mound of stone, 2 ft. base, 1 ft. high, mkd. ¼ on N. face, from which the remains of the original bearing trees:

- A Madrone root crown, bears N.81 3/4°E., 5¼ lks. dist.
- A Fir 43" dia., bears S.84°W., 59 lks. dist., with scribe marks ¼ S visible on partially opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 4 W
1/4 S 26
 S 35
 1980

from which a new bearing tree

- A Fir 17" dia., bears N.68°E., 23 lks. dist. mkd. ¼ S26 BT.

Deposit corner stone alongside iron post.

Fd. OK, April 1995 by G. Lang - M 125-6