TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7818)

Set a stone 12x12x8 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on N. face; from which
A Fir 30" dia., bears S.44°W., 26 lks. dist. mkd. ¼ S BT.
A Maple 12" dia., bears N.28°W., 33½ lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - March 1966 - C.S. File 54/20-25

Found - Orig. 30" D.Fir stump, S.44°W., 17.2 ft., opened for scribed "¼S". (Dist. should be 16.0 ft.)
Orig. 12" Maple, now 17", N.28°W., 22.1 ft., shows scar.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 4 W
¼ S 23 / S 26
1966

Reblaze and rescribe:
17" Maple N.28°W., 22.1 ft.
New BT- 4" D.Fir S.16½°E., 22.0 ft. scribed "¼ S CS BT".
This corner is approx. South of creek.

Fd. brass cap & 2 BTs, April 1995 by Greg Lang - M 125-6

Kris DeGroot - For: Silver Butte Timber - 1/2006 - M 149-41

Found - 1¼" iron pipe by Powell in 1966, firmly set, projecting 12" above the ground, with a 2½" brass cap (properly) stamped. From which an original bearing trees by bushey in 1893:
A 30" D.Fir stump bears S.46°W., 16.0 ft. with scribe marks "¼ S" visible on an opened blaze (rec. S.44°W., 16.0 ft.)
A 19" maple bears N.27°W., 21.9 ft., with a healed blaze.(rec. N.28°W., 22.1 ft.)
New BT - A 8 D.Fir bears S.72°30'W., 30.4 ft. scribed "¼ S26 BT".