

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7820)

Set a stone 14x8x6 ins., 10" in the ground, for ¼ sec. cor. mkd. ¼ on N. face; from which
A Fir 16" dia., bears N.25°W., 27 lks. mkd. ¼ S BT.
A Fir 28" dia., bears S.60½°E., 45½ lks. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Nov. 17, 1959 - C.S. File 42/391-46

Determined by O.B.T.s:
36" Fir S.60°E., 30.0 ft.
24" Fir snag, N.25°W., 17.8 ft.
At corner point, SET 3/4" x 40" Iron pipe, from which
36" Fir bears S.1°E., 61.6 f. mkd. ¼ S23 BT.
40" Fir bears S.3°E., 30.6 ft. mkd. ¼ S23 T31S R4W BT.
24" Fir bears S.82°E., 29.7 ft. mkd. ¼ S23 X BT.
Sec. cor bears West 2664.0 ft. Sec. cor bears East 2408.0 ft.
Corner lies on South end of cat road.

BLM Dependent retracement by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Technician, Group No. 2300 surveyed Jun/July 2008 - (DCSO records 2010-1 plat & copy of map in Vol. 56 Page(s) 21926-7)

The ¼ sec. cor. of secs. 14 & 23, perpetuated by Markham, in 1959, monumented with a bent iron pipe, 3/4" dia., projecting 26" above the ground, from which the remains of an orig. BT
A fir snag, 28" dia., bears S.60½°E., 30.0 ft., with a healed blaze.
and the remains of bearing trees mkd. by Markham
A fir, 25" dia., bears S.83¼°E., 28.1 ft., with scribe marks ¼ S23 T31S R4W BT visible on the bark.
A fir, 40" dia., bears S.4¾°E., 30.0 ft., with scribe marks ¼ S23 X BT visible on the bark.
A fir snag, 32" dia., bears S.3/4°E., 61.1 ft., with a heated blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd. T31S R4W
¼ $\frac{S\ 14}{S\ 23}$
2008
Deposit a magnet in a white plastic case at the base of the stainless steel post, and bury the iron pipe, 40" long, ¾" dia., alongside the stainless steel post.

Cont.

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Fd. to be Ok, July 2012, R. Quimby - C.S. file 65/77-15