

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7822)

A Fir 6" dia., which I mark ¼ S on N. face for ¼ sec. cor., from which

A Fir 8" dia., bears N.31°E., 11½ lks. dist. mkd. ¼ S BT.

A Fir 5" dia., bears S.45°W., 4 lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Nov. 17, 1959 - C.S. File 42/391-47

At midpoint, SET 1¼" x 30" Iron pipe, from which
7" Cedar bears N.1°E., 55.0 ft. mkd. ¼ S11 R4W BT.
10" Fir bears N.70°E., 34.4 ft. mkd. ¼ S11 X BT.
8" Yew bears N.76°E., 32.0 ft. mkd. ¼ S11 X BT.
28" Fir bears N.16°W., 25.8 ft. mkd. ¼ S11 R4W BT.
Small draw bears North 28.0 ft.
Sec. corner bears East 2510.0 ft.
Sec. corner bears West 2582.0 ft.

Ron Quimby - 7/2012 - C.S. File 65/77-13

Found - 1¼" I.Pipe.
New - A 8" D.Fir S.4°W., 6.3 ft. scribed ¼ S14 BT.
A 12" D.Fir N.5°E., 9.6 ft. scribed ¼ S11 BT.
Note - Corner is approx. 150' East of road.