

PRIMARY CORNER DESCRIPTION Angle point on No. bdy. Sec. 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6986)

-----  
Set ¼ sec. post at proper distance, from which  
A Laurel 4" dia., bears S.25°E., 14 lks. dist.  
A Laurel 6" dia., bears N.15°W., 30 lks. dist.

(NOTE: The above corner by Ford must be in doubt due to statement by Thiel in Vol. 17 Pg. 7024 - "In order to be sure that Deputy Ford did not run the South Bdy. of this Tp. and set any Cors., I went to the Cor. of Tps. 30 and 31 S., R. 5 W, on the offset Meridian Line, - -" (V. Laugen, March 1996)

-----  
GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7018)

-----  
Set a Laurel post 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N. face, from which  
A Fir 9" dia., bears S.22°W., 18 lks. dist. mkd. ¼ S BT.  
A Fir 10" dia., bears N.2°W., 18 lks. dist. mkd. ¼ S BT.

-----  
GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Page(s) 7110-11)

-----  
Bushey tied and described cor. set by Thiel)

-----  
BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18131)

-----  
The cor. established as the ¼ sec. cor. of secs. 2 and 35, by Wm. Thiel in 1889 and changed to an angle point by Wm. Bushey in 1893-94, determined from the remains of the original bearing trees:

A Fir root crown, size indeterminate, bears S.22°W., 18 lks. dist., no marks visible.

A Fir 16" dia., bears N.2°W., 18 lks. dist. with mark / visible on opened blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: AP

T 30 S R 4 W

S 35

S 2

T 31 S

(Cont. Next Page)

1985

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 546700

PRIMARY CORNER DESCRIPTION Angle Point on No. Bdy. Sec. 2

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

from which new bearing trees  
A Fir 14" dia., bears S.32½°W., 23 lks. dist., mkd. AP S2  
BT.  
A Fir 19" dia., bears N.59°W., 35 lks. dist., mkd. AP S35  
BT.  
The corner is located on a steep NE. slope, 50 lks. E. of a  
spur, slopes N.

David Edwards - For: Rome Creek Timber LLC - Sept. 2011 -  
M162-72  
-----  
Found - 14" Fir S.32½°W., 15.2 ft.  
20" capped fir stump N.59°W., 23.1 ft.  
24" Fir N.2°W., 11.9 ft.  
Trees have healed blazes.  
Set - 6' steel post 2' East.