

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7802)

Set a stone 14x11x5 ins., 10" in the ground, for cor. to secs. 25, 26, 35 and 36, marked with 1 notch on E. and S. edges; from which

An Oak 10" dia., bears S.61 3/4°W., 205 lks. dist., marked T31S R4W S35 BT.

A Fir 26" dia., bears N.70 3/4°W., 117½ lks. dist., marked T31S R4W S26 BT.

No other trees in limits. Pits impracticable.

Raised mound of stone, 2 ft. high, 2½ ft. base alongside.

BLM Remonumentation by Lynn M. Roseberry, Cadastral Surveyor - Under Group #1000 - Surveyed, Aug. 1980 - (DCSO records Vol. 45 Page(s) 17449)

The sec. cor. monumented with the original basalt stone, 10 x 7 x 5 ins. (rec. 14x11x5 ins.), firmly set 5" in the ground, mkd. with 1 notch on E. and 1 notch on S. edges, from which the remains of the original bearing trees and mound of stone:

A burned root crown with White Oak sprouts, size indeterminate, bears S.61 3/4°W., 205 lks.

A Fir 44" dia., bears N.70 3/4°W., 117½ lks. dist., with scribe marks BT visible on opened and burned blaze.

A mound of stone, 2½ ft. base, 1½ ft. high, bears West, 4 lks. dist.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 31 S R 4 W
S 26 S 25
S 35 S 36
1980

from which new bearing trees:

A Fir 13" dia., bears N.24½°E., 60½ lks. dist. mkd. T31S R4W S25 BT.

A Fir 15" dia., bears S.26°E., 24 lks. dist. mkd. T31S R4W S36 BT.

A Fir 9" dia., bears S.43½°W., 34½ lks. dist. mkd. T31S R4W S35 BT.

A Fir 17" dia., bears N.26¼°W., 35 lks. dist. mkd. T31S R4W S26 BT.

Deposit corner stone alongside iron post.

Fd. Ok - Gerald Nygren - Nov. 1996 - M 124-34