

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7803-04)

Set a stone 16x12x6 ins., 12" in the ground, for cor. to secs. 23, 24, 25 and 26, marked with 1 notch on E. and 2 notches on S. edges; from which

- A Fir 30" dia., bears N.80½°E., 39½ lks. dist. mkd. T31S R4W S24 BT.
- A Fir 14" dia., bears S.32°E., 32½ lks. dist. mkd. T31S R4W S25 BT.
- A Fir 20" dia., bears S.62 3/4°W., 58 lks. dist. mkd. T31S R4W S26 BT.
- A Fir 20" dia., bears N.71½°W., 66½ lks. dist. mkd. T31S R4W S23 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Oct. 16, 1958 - C.S. File 42/391-6

Determined by O.B.T.s:

- 24" Fir snag bears S.32°E., 21.5 ft., found scribe.
- 36" Fir snag bears N.80½°E., 26.0 ft.
- 21" Fir snag bears S.63°W., 38.3 ft.
- 30" Fir snag bears N.71½°W., 45.0 ft.

At corner point, SET 40" long steel fence post, from which

- 6" Fir bears N.50°E., 20.0 ft. mkd. S24 BT.
- 8" Maple bears S.79°E., 135.0 ft. on slope, mkd. S25 R4W BT.
- 6" Fir bears N.65°E., 20.6 ft. mkd. S24 X BT.
- 4" Fir bears S.30°E., 10.0 ft. mkd. S25 BT.

Road bears East 290.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - March 1966 - C.S. File 54/20-4

Found - Steel fence post at sec. corner.

- 6" Fir now 10", N.50°E., 20.0 ft., pitched over, scribe visible.
- 8" Maple now 9", S.79°E., 135.0 ft., scribe visible "S26 R4W 27".
- 6" Fir now 8", N.65°E., 20.6 ft., pitched over, scribe visible.
- 4" Fir now 7", S.30°E., 10.0 ft. scribe visible "S".

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 4 W
 S 23 | S 24
 S 26 | S 25
 1966

(Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - 30" D.Fir S.88°W., 57.3 ft. scribed "T31S R4W S26 CS BT".
Old logging road bears East, 290.0 ft.

Kris DeGroot - For: Silver Butte Timber - 1/2006 - M 149-41

Found - 1¼" iron pipe by Powell in 1966, firmly set, projecting 15" above the ground, with a 2½" brass cap (properly) stamped. From which an orig. BT by Bushey in 1893:
A 28" D.Fir stump bears N.71°45'W., 43.5 ft. with no visible face (rec. N.71½°W., 66½ lks.)
A 28" D.Fir bears N.44°30'E., 19.3 ft. with a healed blaze (rec. N.50°E. 20.0 ft.) 1958 Markham
A 36" splintered D.Fir snag bears S.88°W., 56.2 ft. with scribe marks T31S R4W S26 CSBT" visible. (Rec. S.88°W., 57.3 ft.) Powell 1966

Fd. BC by D. Edwards, 2/2011 - M162-12