

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7805)

Set a stone 12x8x8 ins., 8" in the ground, for 1/4 sec. cor. marked 1/4 on W. face; from which
A Fir 10" dia., bears N.87 3/4°W., 11 lks. dist. mkd. 1/4 S BT.
A Fir 34" dia., bears N.53°E., 34 lks. dist. mkd. 1/4 S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Oct. 29, 1958 - C.S. File 42/391-9

Determined by O.B.T.s
52" Fir bears N.56°E., 23.2 ft.
12" Fir bears N.88°W., 7.3 ft., I rescribed 1/4 S3 X BT.
At corner point, found stone and SET 1/2" x 24" Iron pipe, from which
22" Maple bears S.57°W., 66.0 ft. mkd. 1/4 S23 BT.
32" Fir bears S.72°E., 36.5 ft. mkd. 1/4 S24 BT.
Creek bears East, 100.0 ft.

BLM Dependent retracement by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Technician, Group No. 2300 surveyed Jun/July 2008 - (DCSO records 2010-1 plat & copy of map in Vol. 56 Page(s) 21926-7)

The 1/4 sec. cor. of secs. 23 and 24, perpetuated by Markham, in 1958, determined at record bearing and distance from the remains of an original bearing tree
A sawed fir stump, 49" dia., bears N.53°E., 22.4 ft., with scribe mark S visible on opened blaze.
from which the remains of bearing trees mkd. by Markham
A sawed fir stump, 26" dia., bears S.73 1/4°E., 34.0 ft., with a healed double blaze.
A maple, 39" dia., bears S.57 1/2°W., 64.0 ft., with no marks visible.
A bent iron pipe, 24" long, 1/2" dia, was found lying on the ground nearby.
At the corner point
Set a stainless steel post, 28" long. 2 1/2" dia., 25" in the ground, with brass cap mkd. T31S R4W
1/4
S 23 | S 24
2008
from which
A fir, 12" dia., bears N.9°E., 7.7 ft., mkd. 1/4 S24 BT.
A fir, 18" dia., bears S.50 3/4°W., 19.0 ft., mkd. 1/4 S23 BT.
continued next page

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Deposit a magnet in a white plastic case at the base of the stainless steel post, and bury the iron pipe alongside the stainless steel post.

Fd. BC by D. Edwards, 2/2011 - M162-12