

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Pgs 7805-06)

-----  
Set a stone 14x12x4 ins., 10" in the ground, for cor. to secs. 13, 14, 23 and 24, marked with 1 notch on E. and 3 notches on S. edges; from which

A Fir 11" dia., bears N.71°E., 9½ lks. dist. mkd. T31S R4W S13 BT.

A Fir 15" dia., bears S.69°E., 55 lks. dist. mkd. T31S R4W S24 BT.

A Fir 16" dia., bears S.29°W., 10 lks. dist. mkd. T31S R4W S23 BT.

A Fir 12" dia., bears N.35°W., 39 lks. dist. mkd. T31S R4W S14 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Oct. 2, 1958 - C.S. File 42/391-3

-----  
Determined by O.B.T.s:

30" Fir bears S.29°W., 6.6 ft. I remark on bark "S23 BT"

15" Fir stump bears N.71°E., 6.3 ft.

18" Fir bears S.69°E., 36.3 ft. I remark on bark "S24 BT"

16" Fir bears N.35°W., 25.7 ft. I rescribe on bark S14 BT.

At corner point, found stone and SET Iron pipe, from which

18" Fir bears N.82°E., 29.0 ft. mkd. S13 T31S R4W BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Sept. 28, 1965 - C.S. File 52/40-8

-----  
Found - 1" Iron pipe at corner.

Orig. 30" Fir S.29°W., 6.6 ft., blown down, bark scribed S23.

Orig. 15" Fir stump gone.

Orig. 18" Fir S.69°E., 36.3 ft., blown down.

Orig. 16" Fir N.35°W., 27.5 ft., cut and pushed over. has old bearing tree tag on it.

18" Fir N.82°E., 29.0 ft., blown down. (Markham BT)

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 4 W

S 14 | S 13

S 23 | S 24

1965

New BTs- 32" D.Fir, East 92.3 ft. scribed T31S R4W S24 CS BT

5" D.Fir N.36°E., 22.0 ft. scribed S13 BT.

31" D.Fir N.2½°W., 105.1 ft. "T31S R4W S14 CS BT."

6" D.Fir S.72°W., 40.3 ft. scribed S23 BT.

continued next page

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/20/1998 - C.S. File 66/2-35

- 
- Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 10" above ground, properly marked. 1965
- bears 5" now 16" dia, D.Fir with a fully healed blaze N.34°E., 20.8'. (Rec. N.36°E., 22.0') 1965
- 6" now 14" dia., D.Fir with a fully healed double blaze, bears S.72°W., 38.3' (Rec. S.72°W., 40.3') 1965
- 32" now 33" dia., 2½" high D.Fir stump with a fully healed blaze, bears East, 92.3' Agrees w/rec. 1965
- 31" now blow down found near record "N.2½°W., 105.1 ft" 1965
- New BTs- 7" dia., D.Fir, double blazed and scribed "T31S R4W S24 CS BT" bears S.46½°E., 8.0'
- 5" dia., D.Fir, double blazed and scribed "X CS BT" bears N.53°W., 1.2'.

BLM Dependent retracement by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Technician, Group No. 2300 surveyed Jun/July 2008 - (DCS0 records 2010-1 plat & copy of map in Vol. 56 Page(s) 21926-7)

-----

The cor. of secs. 13, 14, 23 and 24, perpetuated by Markham, in 1958, further perpetuated by the Douglas County Surveyors Office in 1965 and 1998, monumented with an iron post, 1½" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd. from which the remains of original bearing trees

A roothole bears S.69°E., 36.3 ft., with a decayed fir trunk, size indeterminate, lying alongside, with no marks visible.

A roothole bears S.29°W., 6.6 ft., with a fallen fir trunk, 28" dia., lying alongside, with no marks visible.

and the remains of bearing trees mkd. by the Douglas County Surveyors Office in 1965

A fir, 18" dia., bears N.33¾°E., 20.3 ft., with a healed double blaze.

A sawed fir stump, 35" dia., bears N.89¾°E., 92.3 ft. with a healed double blaze.

A fir, 15" dia., bears S.71°W., 39.6 ft., with a healed double blaze.

A roothole bears N.2½°W., 105.1 ft., with a decayed fir trunk, size indeterminate, lying alongside, with no marks visible.

continued next page

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

and BTs mkd. by the Douglas County Surveyors Office in 1998  
A fir, 8" dia., bears S.46¼°E., 7.8 ft., with a healed double blaze.  
A fir, 6" dia., bears N.65°W., 1.4 ft., with a healed double blaze.  
Latitude 42°52'15.20"N Longitude 123°07'53.81"W  
(NAD 1983 (CORS 96))

Fd. to be Ok, July 2012, R. Quimby - C.S. file 65/77-15