

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7807)

Set a stone 16x14x8 ins., 12" in the ground, for ¼ sec. cor., marked ¼ on W. face; from which
A Cedar 13" dia., bears S.47½°W., 23 lks. dist. mkd. ¼ S BT.
A Fir 11" dia., bears N.20½°E., 49 lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Dec. 16, 1958 - C.S. File 42/391-10

Determined by O.B.T.s:
20" Cedar bears S.45°W., 15.2 ft., found scribe.
20" Fir bears N.21°E., 32.3 ft. I bark scribed ¼ S13 BT.
At corner point, found 10" x 10" quartz stone and SET 3/4" x 30" Iron pipe, from which
6" Fir bears S.54°W., 17.2 ft. mkd. ¼ S14 BT.
9" Fir bears S.38°E., 22.0 ft. mkd. ¼ S14 BT.
6" Laurel bears N.22½°E., 27.0 ft. mkd. ¼ S13 BT.

Ron Quimby - 7/2012 - C.S. File 65/77-11

Found - 3/4" I.Pipe & stone.
24" D.Fir stump N.21°E., 32.3 ft. with tin cap.
Down cedar burnt out face.
New - A 6" D.Fir S.8°W., 18.5 ft. scribed ¼ S14 BT.
A 6" D.Fir S.84°E., 2.2 ft. scribed ¼ S 13 BT.