

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7810)

-----  
Set a stone 12x8x8 ins., 8" in the ground for cor. to secs. 1, 2, 11 and 12, marked with 1 notch on E. and 5 notches on S. edges; from which

A Fir 30" dia., bears N.29°E., 60½ lks. dist. mkd. T31S R4W S1 BT.

A Laurel 5" dia., bears S.84½°E., 19 lks. dist. mkd. T31S R4W S12 BT.

A Laurel 4" dia., bears S.20¼°W., 9½ lks. dist. mkd. T31S R4W S11 BT.

A Laurel 9" dia., bears N.61½°W., 49½ lks. dist. mkd. T31S R4W S2 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - May 13, 1959 - C.S. File 42/391-26

-----  
Determined by O.B.Ts:

40" Fir N.27°E., 41.0 ft., found scribe.

Laurel stump S.84°E., 12.5 ft.

Laurel stump S.20°W., 6.3 ft.

At corner point, found stone and SET 1¼" x 36" truck axle, from which:

3" Laurel bears N.17°E., 12.7 ft. mkd. S1 T31S R4W BT.

4" Laurel bears S.77°E., 11.5 ft. mkd. S12 T31S R4W BT.

3" Laurel bears S.17°W., 6.8 ft. mkd. S11 T31S R4W BT.

5" Laurel bears N.83°W., 16.2 ft. mkd. S2 T31S R4W BT.

Small draw bears East, 50.0 ft.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18142)

-----  
The sec. cor., perpetuated and recorded by Markham in 1960, monumented with the original stone, 10x6x6 ins., loosely set, projecting 6" above ground, with 5 notches on the S. and 1 notch on the E. edges, (alongside of which is a flanged axle, 1¼" dia., firmly set, projecting 4" above ground) from which the remains of the original bearing trees:

A Fir 34" dia., N.29°E., 60½ lks. dist., with healed blaze.

A Madrone root crown, bears S.84½°E., 19 lks. dist., no marks visible.

A Madrone root crown, bears S.20¼°W., 9½ lks. dist., no marks visible.

A Madrone root crown, bears N.61½°W., 49½ lks. dist., no marks visible.

(Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

and bearing trees mkd. by Markham:

A Madrone 8" dia., bears S.12½°W., 10½ lks. dist., with fragmentary scribe marks visible on bark blaze.

A Madrone 8" dia., bears N.80°W., 25 lks. dist., with scribe marks BT visible on bark blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31	S R 4 W
S 2	S 1
S 11	S 12
1985	

from which a new bearing tree:

A Fir 6" dia., bears S.60°E., 17 lks. dist. mkd. T31S R4W S12 BT.

Deposit original stone and axle alongside, and white "DEEP-1" magnetic marker at base of stainless steel post.

David Edwards - For: Roseburg Resources - 5/2010 - M 160-63  
-----

Found per 1985 BLM resurvey except the Fir S.60°E., 11.2' is now 12" dia., with healed blaze.

Carl Sweeden - For: Rome Creek Timber - Aug. 2013 - M165-61  
-----

Condition Report

Found - 1985 BLM brass cap

1959 REPORT:

34" D.Fir BT, N.27°E., 39.93' scar vis., tag (1985 also)

Madrone root crown, S.84½°E., 12.54' gone

Madrone root crown, S.20¼°W., 6.27' gone

Madrone root crown, N.61½°W 32.67'

1985 REPORT:

9" Madrone BT, S.12½°W., 6.6', scar vis., tag

7.5" Madrone BT, N.80°W., 16.2', scar vis., tag

13" D.Fir BT, S.60°E., 11.3' Scar vis., tag