

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Pgs 7811-12)

A Fir tree 40" dia., which I mark $\frac{1}{4}$ S on W. face, for $\frac{1}{4}$ sec. cor.; from which

A Maple 9" dia., bears S.88°W., 78 lks. dist. mkd. $\frac{1}{4}$ S BT.

A Maple 8" dia., bears N.47°E., 29 lks. dist. mkd. $\frac{1}{4}$ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. -
Wit: R.G. Boyd - May 13, 1959 - C.S. File 42/391-28

Determined by O.B.T.s:

10" Maple S.88°W., 51.5 ft., found scribe.

10" Maple N.47°E., 19.2 ft., found scribe.

At corner found 60" Fir mkd. on West face and
Set $\frac{3}{4}$ " x 30" iron pipe, from which,

3" Hemlock bears S.44°E., 33.1 ft. mkd. $\frac{1}{4}$ S1 BT.

48" Fir bears S.41°E., 35.2 ft. mkd. $\frac{1}{4}$ S1 R4W BT.

6" Hemlock bears S.63°E., 44.0 ft. mkd. $\frac{1}{4}$ S1 BT.

12" Maple bears N.39°W., 43.0 ft. mkd. $\frac{1}{4}$ S2 BT.

Creek bears North, 10.0 ft. dist.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18143)

The $\frac{1}{4}$ sec. cor., perpetuated and recorded by Markham in 1960, monumented with the original corner tree, a Fir 57" dia., with healed blaze on W. face, from which the original bearing trees:

A Maple 14" dia., bears N.43 $\frac{1}{2}$ °E., 22 lks. dist., with axe marks visible on decayed blaze. (Rec. N.47°E., 78 lks.)

A Maple 14" dia., bears S.82 $\frac{1}{4}$ °W., 70 lks. dist., no marks visible, (Rec. S.88°W., 29 lks.)

and bearing trees mkd. by Markham:

A Hemlock 11" dia., bears S.60°E., 60 lks., with healed double blaze.

A Fir 39" dia., bears S.36°E., 50 lks. dist., with scribe marks $\frac{1}{4}$ S1 R4W visible on bark blaze.

and a new reference monument:

A stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., set 22" in the ground for a reference monument, bears West, 15 lks. dist., with brass cap mkd. RM T31S R4W 10 FT TO COR TREE S2 1985, with an arrow pointing to the corner.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Cont.

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Carl Sweeden - For: Rome Creek Timber - Aug. 2013 - M165-61

Condition Report

Found - 62" fir corner tree w/ various scars and tags & "X"
in bark on west side
14" Maple BT stump, S.82¼°W., 46.2'
15" Maple BT, N.43½°E., 14.52' scar vis., tag
15" Hemlock BT, S.60°E., 39.6', scar vis., tag
44" Fir BT, S.36°E., 33', bark blazed
Stainless steel post up 0.5' with 3¼" BC "M CAP"
west 9.9'