

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION C C for Secs. 1 & 2 only, No. Bdy

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7812-13)

-----  
At point of intersection (5.25 chs. W. of the cor. to secs. 1, 2, 35 and 36) Set a stone 15x12x3 ins., 10" in the ground, for closing cor. to secs. 1 and 2, marked CC on S. face, with 1 notch on E. and 5 notches on W. faces; from which  
A Maple 6" dia., bears S.45½°E., 24½ lks. dist. mkd. T31S R4W S1 BT.  
A Fir 30" dia., bears S.72½°W., 16 lks. dist. mkd. T31S R4W S2 BT.  
A Fir 34" dia., bears N.69¼°E., 52 lks. dist. mkd. T31S R4W CC S1 and 2 BT.

Survey by John H. Markham, Jr. - Wit: R.G. Boyd - For: Stomar Lumber Co. - Feb/March 1959 - C.S. File 42/391-12

-----  
Determined by O.B.T.s  
10" Maple snag bears S.45°E., 16.1 ft.  
36" Fir bears S.72°W., 10.6 ft.  
34" Fir bears N.69°E., 34.3 ft.  
At corner point, SET 3/4" x 30" Iron pipe, from which  
9" Laurel bears N.89°E., 21.5 ft. mkd. S1 T31S R4W BT  
12" Laurel bears N.54°E., 34.0 ft. mkd. S35 T30S R4W BT  
5" Laurel bears N.69°W., 16.1 ft. mkd. S35 BT.  
CC sec. cor. for 35 and 36, bears East 344.0 ft.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18144-45)

-----  
True point for the closing cor. of secs. 1 and 2.  
Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd. T 30 S R 4 W

S 35  
-----  
S 2 | S 1  
T 31 S R 4 W  
1985

from which  
A Fir 8" dia., bears S.71°E., 7 lks. dist. mkd. T31S R4W S1 CC BT.  
A Fir 6" dia., bears S.72°W., 35 lks. dist. mkd. T31S R4W S2 CC BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

(Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION CC for Secs. 1 and 2 only, No Bdy

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this point, the original closing cor. of secs. 1 and 2, bears N.0°35'E., 0.10 chs. dist., perpetuated and recorded by Markham in 1959, monumented with the original corner stone, 13 x 10 x 5, lying loose on the ground, mkd. CC on face, (alongside of which is an iron pipe, 1" dia., firmly set, projecting 4" above ground), from which the original bearing trees:

A Fir 26" dia., bears N.71½°E., 48 lks. dist., with healed blaze. (Rec. N.69¼°E., 52 lks.)

A Fir 40" dia., bears S.68°W., 15 lks. dist., with healed blaze. (Rec. S.72½°W., 16 lks.)

and bearing trees mkd. by Markham:

A Madrone 14" dia., bears N.55°E., 46 lks. dist., with scribe marks BT S35 T30S R4W visible on bark blaze.

A Madrone 12" dia., bears S.89½°E., 29 lks. dist., with scribe marks BT S1 T31S R4W visible on bark blaze.

A Madrone 9" dia., bears N.69½°W., 23 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.

From the same point, the cor. of secs. 35 and 36 only, T30S R4W bears N.89°31'E., 5.295 chs. dist.

David Edwards - For: Rome Creek Timber LLC - Sept. 2011 - M162-72

-----  
Found - 14" Fir S.71°E., 4.6'  
          10" Fir S.72°W., 23.1'  
          Both with healed blaze.  
Set - 6' steel post 2' West.