

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 606700

PRIMARY CORNER DESCRIPTION Sec. cor. for 35 & 36 only, T30-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6986-87)

Set a post at proper distance, cor. of secs. 1, 2, 35 and 36, from which

- A Laurel 14" dia., bears S.50°E., 16 lks. dist.
- A Laurel 8" dia., bears N.35°E., 28 lks. dist.
- A Red Fir 10" dia., bears N.12°W., 19 lks. dist.
- A Red Fir 16" dia., bears S.45°W., 40 lks. dist.

(NOTE: The above corner by Ford must be in doubt due to statement by Thiel in Vol. 17 Pg. 7024 - "In order to be sure that Deputy Ford did not run the South Bdy. of this Tp. and set any Cors., I went to the Cor. of Tps. 30 and 31 S., R. 5 W., on the offset Meridian Line, - - - -" (V. Laugen, March 1996)

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7017) and Pg. 7030)

For cor. to secs. 1, 2, 35 and 36, I mark a Laurel, 5" dia., T30S S36 on NE.; R4W S1 on SE.; T31S S2 on SW.; S35 on NW. faces, with 1 notch on E. and 5 notches on W. edges, from which

- A Laurel 4" dia., bears N.41 3/4°E., 17 lks. dist. mkd. T30S R4W S36 BT.
- A Laurel 6" dia., bears S.41 1/2°E., 19 lks. dist. mkd. T31S R4W S1 BT.
- A Fir 9" dia., bears S.31°W., 35 lks. dist. mkd. T31S R4W S2 BT.
- A Fir 10" dia., bears N.59 3/4°W., 62 lks. dist. mkd. T30S R4W S35 BT.

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Pg. 7110) and (Vol. 18 Page(s) 7813)

(Pg. 7110)
(Bushey tied and described cor. by Thiel)
(Pg. 7813)

As the old cor. established for secs. 1, 2, 35 and 36 is not a cor. to secs. 1 and 2, I destroy the marks on the SE. and SW. faces of the tree cor. and also the marks on the 2 Laurel witness trees S. of the cor. in T31S R4W.

(Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 606700

PRIMARY CORNER DESCRIPTION Sec. cor. for 35 & 36 only, T30-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by John H. Markham, Jr. - Wit: R.G. Boyed - For:
Stomar Lumber Co. - Feb. 24, 1959 - C.S. File 42/356-10

As determined by O.B.T.
24" Fir bears S.31°W., 23.1 ft.
10" Laurel snag bears S.41°E., 12.5 ft.
At corner point SET 3/4" x 30" Iron pipe, from which
13" Fir bears S.76°W., 4.5 ft. mkd. S1 X BT.
12" Fir bears N.63°W., 7.5 ft. mkd. S35 BT.
7" Laurel bears N.75°E., 20.1 ft. mkd. S36 T30S R4W BT.
CC sec. cor. for 2 and 1 bears West 344.0 ft.
East 1/4 cor. S. 35 bears North 381.0 ft.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J.
Bishop, Cadastral Surveyors, under Group #1217, surveyed
Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18130)

The sec. cor., perpetuated and recorded by Markham in 1960,
monumented with an iron pipe, 1" dia., firmly set, projecting
12" above ground, from which the remains of the original
bearing trees:

A Fir 27" dia., bears S.31°W., 35 lks. with healed blaze.
and bearing trees mkd. by Markham
A Madrone 10" dia., bears N.74 1/4°E., 30 lks., with scribe
marks T30S R4W S36 BT.
A Fir 17" dia., bears S.81 3/4°W., 7 1/2 lks., with healed
blaze.
A Fir 17" dia., bears N.59 1/2°W., 12 lks. with healed blaze.

At the corner point
Set an stainless steel post, 28" long, 2 1/2" dia., 22" in
the ground, with brass cap mkd:

T 30 S R 4 W
S 35 | S 36
S 1
T 31 S R 4 W
1985

Deposit iron pipe alongside and white "DEEP-1" magnetic
marker at base of stainless steel post.

David Edwards - For: Rome Creek Timber LLC - Sept. 2011 -
M162-72

Found - 10" Madrone N.74°E., 19.8' }
30" Fir S.31°W., 23.1' } Firs have
18" Fir S.82°W., 5.0' } healed blazes
17" Fir N.59 1/2°W., 7.9' }
Set - 6' steel post 2' north.