

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 620340

PRIMARY CORNER DESCRIPTION C W 1/16 cor. Sec. 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. -
Wit: R.G. Boyd - Oct.29, 1958 - C.S. File 42/391-7

At corner point, SET 1/2" x 24" Iron pipe, from which
40" Fir bears S.1°E., 35.0 ft. mkd. 1/16 S24 BT.
40" Fir bears S.29°W., 42.0 ft. mkd. 1/16 S24 BT.
West 1/4 cor. sec. 24 bears West 1313.0 ft.

David Edwards - For: Roseburg Resources Co. - Feb. 2011 -
M162-12

Set - 5/8"x30" steel rebar w/2½" dia., alum cap mkd as per
BLM manual & marked "ROSEBURG RESOURCES CO." "LS
2339" and "2011"
A 6" diam. Fir bears N.89°E., 5.1 ft.
A 10" dia. Fir bears N.47°W., 3.6 ft.
A 6 ft steel post is set 2 south.

Note- Monuments set by Markham in 1958 (see field notes in
C.s. file 42/391), are significantly out of position and are
therefore disregarded.