

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7802-03

-----  
Set a Fir post, 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on N. face; from which  
A Fir 12" dia., bears S.18°W., 7 ¾ lks. dist. mkd. ¼ S BT.  
A Fir 10" dia., bears N.6¼°W., 36 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - April 1966 - C.S. File 54/20-44

-----  
Found - 10" Fir now 18", N.6¼°W., 23.8 ft., tree opened for scribe.

Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 4 W  
¼ S 25  
S 36  
1966

New BTs- 22" D.Fir N.12½°E., 31.5 ft. scribed ¼ S25 CS BT.

7" Cedar S.61°W., 28.4 ft. scribed ¼ S36 CS BT.

This corner lies on S. slope of ridge, running about E & W., 50 ft. N. of small draw. It is now on edge of cut unit.

Fd. OK, April 1993 by R. Brown - M 112-72

Troy Rambo - June 2001 - C.S. File 65/37-22B

-----  
Found - 1966 DCSO brass cap at the ¼ cor. and rec. BTs  
The rec. Fir, N.12½°E., 31.5 ft. is now a burnt stump with a healed face.

Scribed- "BT" at the base & chopped and "X" at dbh on a 4" DF  
- bears N.82°W., 8.8 ft.

"BT" at the base & chopped and "X" at dbh on a 5" DF  
- bears S.22°E., 21.1 ft.

A 5½" steel fence post bears 1.0 ft. West.