

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol 18 Pages 7806-07)

Set a stone 14x12x8 ins., 10" in the ground for ¼ sec. cor. marked ¼ on N. face, from which

A Fir 9" dia., bears N.17¼°E., 16 lks. dist. mkd. ¼ S BT.

A Fir 14" dia., bears S.28½°E., 20 lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Oct. 2, 1958 - C.S. File 42/391-2

Determined by O.B.T.s:

30" Fir S.25°E., 13.2 ft. dist.

16" Fir N.18°E., 11.5 ft., I rescribe ¼ S13 BT.

At corner point, found stone and SET 1" x 30" Iron pipe from which:

17" Fir bears S.78°E., 9.6 ft. mkd. ¼ S24 BT.

7" Maple bears N.16°E., 54.4 ft. mkd. ¼ S13 BT.

Creek bears West 516.0 ft. dist.

BLM Dependent retracement by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Technician, Group No. 2300 surveyed Jun/July 2008 - (DCSO records 2010-1 plat & copy of map in Vol. 56 Page(s) 21926-7)

The ¼ sec. cor. of secs. 13 & 24, perpetuated by Markham, in 1958, determined at record bearing & distance from the remains of an original bearing tree

A sawed fir stump, 24" dia., bears N.17¼°E., 10.6 ft., with fragmentary scribe marks visible on the bark.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd.

T31S R4W

¼ $\frac{S\ 13}{S\ 24}$

2008

from which

A fir, 12" dia., bears N.13½°E., 32.0 ft., mkd. ¼ S13 BT.

A fir, 5" dia., bears N.85°W., 11.1 ft. mkd. ¼ S24 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located in large rock slide area, on a steep SW. slope.

Fd. BC by D. Edwards, 2/2011 - M162-12