

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7811)

A Fir tree, 6" dia., which I mark $\frac{1}{4}$ S on N. face, for $\frac{1}{4}$ sec. cor.; from which

A Fir 15" dia., bears S.26 $\frac{1}{2}$ °E., 14 $\frac{3}{4}$ lks. mkd. $\frac{1}{4}$ S BT.

A Fir 30" dia., bears N.4 $\frac{1}{2}$ °E., 19 $\frac{1}{2}$ lks. mkd. $\frac{1}{4}$ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. -
Wit: R.G. Boyd - Sept. 1960 - C.S. File 42/391-54

Determined by O.B.T.s:

50" Fir N.4°E., 12.7 ft. I bark scribe $\frac{1}{4}$ S1 BT.

36" Fir S.26°E., 9.8 ft.

At corner point, SET 1/2" x 24" iron rod, from which

12" Fir bears N.43°E., 15.7 ft. mkd. $\frac{1}{4}$ S1 BT.

14" Laurel bears N.88°E., 20.0 ft. mkd. $\frac{1}{4}$ S1 T31S R4W BT.

14" Laurel bears S.15°E., 22.0 ft. mkd. $\frac{1}{4}$ S12 BT.

9" Fir bears S.74°W., 14.0 ft. mkd. $\frac{1}{4}$ S12 BT.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18141)

The $\frac{1}{4}$ sec. cor., perpetuated and recorded by Markham in 1960, monumented with an iron rod, $\frac{1}{2}$ " dia., firmly set, projecting 4" above ground, from which the original BTs:

A Fir 17" dia., bears N.4 $\frac{1}{2}$ °E., 19 $\frac{1}{2}$ lks., with healed blaze and rescribed by Markham, with scribe marks $\frac{1}{4}$ S1 BT visible on bark blaze.

A Fir 33" dia. bears S.26 $\frac{1}{2}$ °E., 14 $\frac{3}{4}$ lks. with healed blaze. and bearing trees mkd. by Markham:

A Fir 20" dia. bears N.42 $\frac{3}{4}$ °E., 23 $\frac{1}{2}$ lks. with healed blaze.

A Madrone 21" dia. bears N.88°E. 29 $\frac{1}{2}$ lks with healed blaze

A Fir 17" dia., S.74°W., 21 lks., with healed blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, directly over the iron rod, with brass cap mkd:

T 31 S R 4 W

$\frac{1}{4}$ $\frac{S 1}{S 12}$
1985

David Edwards - For: Roseburg Resources - 5/2010 - M 160-63

Found as per 1985 BLM resurvey except the OBT N.4 $\frac{1}{2}$ °E., 12.9' is 40" dia.