

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; & 30 of T31-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7793)

-----  
A Laurel 3" dia., which I mark  $\frac{1}{4}$  S on W. face for  $\frac{1}{4}$  sec. cor., from which

A Fir 30" dia., bears S.50 $\frac{1}{2}$ °E., 72 $\frac{1}{2}$  lks. dist. mkd.  $\frac{1}{4}$  S BT

A Fir 24" dia., bears S.63 $\frac{1}{2}$ °W., 78 $\frac{1}{2}$  lks. dist. mkd.  $\frac{1}{4}$  S BT

-----  
Douglas Co. Surveyors Office - George Wenderoth, Deputy - 1946-47 - M 27-14

-----  
Found - Old BT, a 40" Fir bearing S.50°30'E., 47.8 ft.

Drive a 1 $\frac{1}{2}$ " I.P. for corner and mark BT:

20" Madrone bearing N.29°49'W., 21.7 ft.

-----  
Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Feb/March 1966 - C.S. File 54/20-36

-----  
Found - I.P. at  $\frac{1}{4}$  corner.

Orig. 40" Fir, S.50 $\frac{1}{2}$ °E., 47.8 ft, shows good scar, opened for scribing.

20" now 23" Laurel N.29°49'W., 21.7 ft. (bearing should be N.32°W.), scribing visible " $\frac{1}{4}$  S CS BT"

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S

R4W  $\frac{1}{4}$  S25|S 30 R3W

1966

New BT - 7" Laurel S.53°E., 4.7 ft. scribed  $\frac{1}{4}$  S30 CS BT.

-----  
Carl Sweeden - For: Perpetual Forest Co - 3/2011 - M162-13

-----  
Found - 2 $\frac{1}{2}$ " BC, 1966 DCSO w/1 $\frac{1}{2}$ " I.P. along side.

27" madrone BT, N.30°W. 22.0' partly open face, tag.

41" D.Fir BT, S.50°E., 47.8', partly open face, tag.

12" Madrone BT, S.53°E., 4.7', scar vis. tag.

-----  
FD. Ok by C. Sweeden, 3/2012 - M163-35