

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T31-3

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7796-97

Set a stone 16x14x10 ins., 11" in the ground for cor. to secs. 1, 6, 7 and 12, marked with 1 notch on N. and 5 notches on S. edges; from which
A Fir 16" dia., bears N.89°E., 73½ lks. dist. mkd. T31S R3W S6 BT.
A Fir 30" dia., bears S.73°E., 87 lks. dist. mkd. T31S R3W S7 BT.
A Fir 20" dia., bears S.68°W., 35 lks. dist. mkd. T31S R4W S12 BT.
A Fir 30" dia., bears N.85°W., 61 lks. dist. mkd. T31S R4W S1 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Aug. 2, 1960 - C.S. File 42/392-65

Corner determined by original BTs:
40" Fir S.73°E., 57.4 ft.
22" Fir snag, S.68°W., 23.1 ft.
40" Fir N.85°W., 40.2 ft.
At corner point, found Stone and SET 3/4" x 30" I.P., from which
4" Laurel S.87°W., 11.3 ft. mkd. S12 T31S R4W BT.
5" Laurel N.53°W., 7.7 ft. mkd. S1 T31S R4W BT.
5" Laurel N.12°E., 7.1 ft. mkd. S6 T31S R3W BT.
5" Laurel, East 17.2 ft. mkd. S7 T31S R3W BT.
5" Laurel S.10°W., 11.0 ft. mkd. S12 T31S R4W BT.
(¼ cor. for 6 & 7 bears N.82½°E.)

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18137)

The Sec. cor., perpetuated and recorded by Markham in 1960, monumented with the original stone, 15x12x8 ins., firmly set, projecting 8" above ground, with a notch on N. and 5 notches on S. edges, (alongside of which is an iron pipe, 3/4" dia., firmly set, projecting 4" above ground,) from which the remains of the original bearing trees:
A Fir 43" dia., bears S.73°E., 87 lks., with healed blaze.
A Fir snag, size indeterminate, bears S.68°W., 35 lks. dist., no marks visible.
A Fir 47" dia., bears N.85°W., 61 lks., with healed blaze.
and bearing trees mkd. by Markham:
continued next page

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T31-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

- A Madrone 8" dia., bears N.12°E., 10 lks. dist., with scribe marks T31S R3W S6 BT visible on bark blaze.
- A Madrone 8" dia., bears S.89°E., 25 lks. dist., with scribe marks T31S R3W S7 BT visible on bark blaze.
- A Madrone 8" dia., bears S.10½°W., 18 lks. dist., with scribe marks T31S R4W S12 BT visible on bark blaze.
- A Madrone 8" dia., bears S.87°W., 17 lks. dist., with scribe marks T31S R4W S1 BT visible on bark blaze.
- A Madrone 8" dia., bears N.49°W., 11½ lks. dist., with scribe marks T31S R4W S1 BT visible on bark blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 31 S	
R 4 W	R 3 W
S 1	S 6
S 12	S 7
1985	

Deposit corner stone and iron pipe alongside, and white "DEEP-1" magnetic marker at base of stainless steel post. From this point, United States Geological Survey triangulation station "BLAND MTN 1953", bears N.4°30'30"W., 387.455 chs. dist., monumented with a standard brass tablet, 3½" dia., cemented flush with top of bedrock, with top mkd. US GEOLOGICAL SURVEY BLAND MT. 1953 and a triangle.

Mark Smalley - R. McManis - 11/19/2002 - C.S. file 65/44-26

Condition report only.

Found - Corner stone & iron pipe with 1985 brass cap properly marked.

43" D.Fir orig. BT in good condition bears S.73°E., 57.4 ft.

47" D.Fir orig. BT in good condition bears N.85°W., 40.3 ft.

Rotten stub bears S.68°W., 23.1 ft.

7" Madrone (rec. 8") bears N.49°W., 7.6 ft., good bark scribe vis.

6" Madrone (rec. 8") bears N.12°E., 6.6 ft. - good health, bark scribe visible.

7" Madrone (rec. 8") bears S.89°E., 16.5 ft. - good health, bark scribe visible.

6" Madrone (rec. 8") bears S.10°W., 11.96 ft. - good health, bark scribe visible

6" Madrone (rec. 8") bears S.87°W., 11.2 ft. - good health, bark scribe visible

Fd. as per 2002 report - D.Edwards, 5/2010 - M160-63