

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & 6 of T31-3

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7797)

-----  
Set a stone 16x14x12 ins., 12" in the ground, for 1/4 sec. cor. marked 1/4 on W. face; from which  
A Fir 33" dia., bears S.57 1/4°W., 25 1/2 lks. dist. mkd. 1/4 S BT  
A Fir 5" dia., bears N.61 1/4°E., 23 lks. dist. mkd. 1/4 S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Aug. 2, 1960 - C.S. File 42/392

-----  
Corner determined by original BTs:  
40" Fir snag S.57°W., 16.8 ft.  
22" Fir N.61°E., 15.2 ft.  
At corner point Found Stone mkd. 1/4 and SET 3/4" x 30" I.P., from which  
12" Maple N.44°E., 10.0 ft. mkd. 1/4 S6 BT.  
4" Fir N.75°E., 11.8 ft. mkd. 1/4 S6 BT.  
7" Fir S.58°E., 19.0 ft. mkd. 1/4 S6 BT.  
10" Laurel S.58°W., 18.5 ft. mkd. 1/4 S1 R4W BT.  
2" Fir N.49°W., 6.2 ft. mkd. 1/4 S1 BT.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18138)

-----  
The 1/4 sec. cor., perpetuated and recorded by Markham in 1960, monumented with the original stone, 16x14x12 ins., loosely set, projecting 10" above ground, no marks visible, (alongside of which is an iron pipe, 1/2" dia., firmly set, projecting 10" above ground,) from which the remains of the original bearing trees:

A Fir 30" dia., bears N.61 1/4°E., 23 lks. dist., with healed blaze.  
A decayed Fir stump, size indeterminate, bears S.57 1/4°W., 25 1/2 lks. dist., no marks visible.  
and the remains of the bearing tree mkd. by Markham:  
A root hole, bears N.44°E., 15 lks. dist. with down Maple alongside, 14" dia., with healed blaze.  
A root hole bears S.58°E., 29 lks. dist. with down Fir alongside, 8" dia., with scribe marks 1/4 S6 BT visible on partially healed blaze.  
A Madrone 14" dia., bears S.59°W., 29 lks. dist. with scribe marks 1/4 S1 BT visible on bark blaze.  
A Fir 6" dia., bears N.49°W., 10 lks. dist. , with healed blaze.

At the corner point

(Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & 6 of T31-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 31 S  
R 4 W R 3 W  
1/4  
S 1 S 6  
1985

Deposit corner stone and iron pipe alongside, and white "DEEP-1" magnetic marker at base of stainless steel post.