

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION C C for Sec. 1; & S. 6, T31-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 - (DCSO records Vol. 18 Page(s) 7798)

At point of intersection, set a stone, 16x12x10 ins., 12" in the ground for closing cor. to Tp. 31 S., Rs. 3 and 4 W. marked C C on S. face, with 6 notches on SE. and W. faces; from which

A Fir 36" dia., bears S.55½°E., 34¼ lks. dist. mkd. T31S R3W S6 BT.

A Maple 14" dia., bears S.67°W., 64½ lks. dist. mkd. T31S R4W S1 BT.

A Fir 36" dia., bears N.34½°E., 37½ lks. dist. mkd. T31S R3W and 4 W C C BT.

Douglas Co. Surveyors Office - James Byron, Deputy and crew -March 1963 - C.S. File 52/138-45

Found - Orig. 14" now 24" Maple S.67°W., 42.5 ft., shows good scribing.

Orig. 36" now 40" Fir S.55½°E., 22.6 ft., shows scribing.

Orig. NE. BT, shows scar.

We find corner stone as recorded.

Set Brass cap alongside cor. stone & mkd:

County Surveyors Office

R4W T30S R3W

C C

S 1 | S 6

T31S

Rescribe now 24" Maple, S.67°W., 43.0 ft. "T31S S1 CS BT CC"

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18139-40)

(39.90 chs., N.0°02'W., from ¼ sec. cor.)

True point for the closing cor. to Tps. 31S., Rs. 3 and 4W.

Set a stainless steel post, 28" long 2½" dia., 22" in the ground, with brass cap mkd:

T 30 S R 3 W

S 1 | S 6

C C

R 4 W R 3 W

T 31 S

1985

Deposit white "DEEP-1" magnetic marker at base of stainless steel post. (Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION C C for Sec. 1; & S. 6 of T31-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this point, the original closing cor. of Tps. 31 S., Rs. 3 and 4 W., bears N.0°02'W., 0.027 chs. dist. perpetuated and recorded by Byron in 1963, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T30S R3W R4W CC S1 S6 T31S 1963, from which the original bearing trees:

A Fir 52" dia., bears N.34½°E., 37½ lks. dist., with healed blaze.

A Fir 43" dia., bears S.55½°E., 34¼ lks. dist. with healed blaze.

A Maple 23" dia., bears S.67°W., 64½ lks. dist., with scribe marks 31S R4W S1 visible on opened blaze. Rescribed by Byron.