

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION ¼ Cor. for 31; & 36 of T31-6

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records, Vol. 19 Page 7880)

-----  
Set ¼ sec. post, from which:

- A Fir, 4" dia., bears S.45°E., 31 lks. dist.
- A Fir, 6" dia., bears N.21°W., 25 lks. dist.

George J. Wenderoth, Deputy County Surveyor - Feb. 5, 1959  
C.S. File 49/92-4

- 
- Found - 15" Fir, N.21°W., 16.5 ft. good shape.  
Remains of Fir S.45°E., 19.5' & scribe marks plain.
  - Set - Drive 1" Iron Pipe for corner.
  - New BT - 12" Hemlock S.82°24'E., 23.3', scribed.

Lloyd "David" Smith - For: State of Oregon, Dept. of Forestry  
- June 1998 - M 129-8

- 
- Found - 1" I.P., 1959
  - 6" Fir, (Orig.), N.21°W., 25 lks. Now 4"x10" piece of root crown intact, BT stump missing.
  - 12" Hemlock, 1959, S.82°24'E., 23.3'. Now 15"x1' high rotten stump in place, face rotted with some axe work visible.

Re-witnessed -

- Orange carsonite marker CBM-250 labeled witness post, S.18°E., 6.2', to base.
- Orange carsonite marker CBM-250 labeled witness post, S.70°E., 4.5', to base.
- Orange carsonite marker CBM-250 labeled witness post, N.72°W., 4.1', to base.
- Orange carsonite marker CBM-250 labeled witness post, N.20°W., 4.5', to base.

Note - Logged and burned on both sides of line.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2883, surveyed March 2018/April 2018 - (DCSO records Vol. 59 Page(s) 23927-28)

-----  
The ¼ sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp., perpetuated by Wenderoth, in 1959; subsequently perpetuated by Smith, in 1998; from original evidence no longer in existence; monumented with an iron pipe, 1¼" dia., firmly set, projecting 9 ins. above ground.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, directly over the iron pipe, 28" long, with brass cap mkd.  
Continued next page

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION ¼ Cor. for 31; & 36 of T31-6

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

T31 S  
R6W R5W  
¼  
S 36 | S 31  
2018

from which

A fir, 10" dia., bears S.77°E., 16.5 ft., mkd. ¼ S31 BT.

A fir, 11" dia., bears S.20¾°W., 11.5 ft., mkd. ¼ S36 BT.

Corner is located on an E. slope.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.