

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec Cor. 18 & 19; 13 & 24 T31-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Geo. W. Hyde under contract #54, dated Feb. 19, 1855. (DCSO records Vol. 19, Pg. 7878)

Set post from which:

- A Laurel, 8" dia. bears N.41°W., 41 lks.
- A Laurel, 6" dia. bears S.55°W., 64 lks.
- A Live Oak, 10" dia. bears N.43°E., 40 lks.
- A Fir, 36" dia. bears S.29°E., 55 lks.

Victor S. King, witness: Chester C. Jones - for: Bate Lumber Co. Feb. 5, 1959 - C.S. File 42/425-7

Found -

- 10" Live Oak, N.43°E., 40 lks. with scribing. (orig. BT.)
- 8" Laurel, N.41°W., 41 lks. This BT is dead & rotten, but shows old scar from blaze. (orig. BT.)

Set 1½" Iron Pipe 3' long from which I set the following BTs:

- 5" Fir, N.44°E., 28.9 ft. scribed "T31 R5 S18 BT"
- 11" Live Oak, S.61°E., 35.7 ft. scribed "T31 R5 S19 BT"
- 10" Live Oak, S.46°W., 15.4 ft. scribed "T31 R6 S24 BT"
- 6" Fir, N.63°W., 14.4 ft. scribed "T31S R6 S23 BT"

Doug. County Surveyors Office - John M. Powell, Frank Jones and Joe Brady, May - June 1966, C.S. 54/25-29

Found 1½" Iron Pipe at corner from which:

- 10" Live Oak, N.43°E., 26.4 ft. opened for scribe "BT" (orig. BT.)
- 8" Laurel, dead, N.41°W., 27.1 ft. opened for parts of scribe. (orig. BT.)
- 10" Live Oak, N.43°E., 24.7 ft. scribed "BT"
- 8" Laurel, N.44½°W., 28.1 ft. scribe marks
- 5" Fir, now 6", N.44°E., 28.9 ft. pitched over scribing.
- 11" Live Oak, now 12", S.61°E., 35.7 ft. scribed "T31S R5W S19 BT"
- 10" Live Oak, S.46°W., 15.4 ft. scribed T31S R6W S24 BT.

Set Brass Cap at Corner marked: COUNTY SURVEYORS OFFICE

R	T31S	R
6	S 13 S 18	5
W	S 24 S 19	W
1966		

New Accessories -

- King's 1½" Iron Pipe N.43°E., 1.7 ft.
- 6" Fir, N.44°E., 30.4 ft. shows good scribing.

Continued next page

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Cor. to 18 & 19; 13 & 24 T31-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" live Oak S.65°E., 36.1 ft. shows good scribing.
11" Live Oak North, 25.7 ft. Scribed "T31S R6 S13 CS BT."
11" Live Oak S.42°W., 14.1 ft. shows good scribing.

Bruce Shaner, L.S.. #430 - For: Richard McKenzie - John Wright - Clem Berlier - Oct. 1993 - M 117-76 - C.S. File 63/153-43

Found - 2½" Brass cap on a 1" Iron Pipe from which:

1½" Iron Pipe bears N.44°E., 1.7'.
8" D.Fir, face overgrown, bears N.47°E., 29.7' (rec. N.44°E., 30.4').
12" Live Oak, face overgrown, bears S.65°E., 36.1'.
11" Live Oak, scribes visible, bears N.7°E., 25.1' (rec. North, 25.7').
11" Live Oak, stump, scribes visible, bears S.42°W., 14.1'.
12" Live Oak, face rotted out, bears N.47°E., 25.4' (rec. N.43°E., 26.4')

New Accessories -

12" D.Fir, scribed "T31S R6W S24 BT", bears S.68°W., 60.4'.
10" Live Oak, scribed "T31S R6W S13 BT", bears N.32°W., 48.6'.

Note - Corner lies North 230' above spur logging road.

Found OK by Greg Lang, Oct. 1997 - M 128-18

Fd. Ok by BLM dependent resurvey by Daniel E. Weller, Cadastral Surveyor, under Group #1884, surveyed July/Sept 1998. (DCSO records Vol. 53 Page(s) 20468-9)

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2078, surveyed June/Sept. 2004 (DCSO rec. Plat 31-6 2011 & Vol. 56 pg(s) 22322)

The cor. of secs. 13, 18, 19, & 24 on the E bdy of the Tp monumented with an iron pipe, 1½" dia., firmly set, projecting 12" above the ground, w/brass cap (properly) mkd. from which the remains of an orig. BT

An Oak, 13" dia., bears N.45°E., 26.4 ft. with a decayed blaze.

and the remains of BTs mkd by King in 1959, reported by Weller in 1998

A fir, 11" dia., bears N.44°E., 29.7 ft. with a healed blaze.

continued next page

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec Cor. 18 & 19; 13 & 24 T31-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An oak 14" dia., bears S.64°E., 36.0 ft. with a healed blaze.
An Oak stump, 10" dia., bears S.43¾°W., 13.5 ft. with illegible scribe marks visible on an partially healed blaze.
and the remains of a BT mkd by Powell, and an accessory set by King, moved and reset by Powell in 1966, reported by Weller in 1998
An Oak snag, 10" dia., bears N.4°E., 25.1 ft. with scribe marks T31S R6W S BT visible on a partially healed blaze
An iron pipe 1½" dia., firmly set projecting 12" above the ground, bears N.43°E., 2.0 ft.
and a BT mkd by Shaner in 1993, reported by Weller in 1998
An Oak 10" dia., N.37¾°W., 48.5 ft. with scribe marks T31S R6W S13 BT visible on a partially healed blaze.