

PRIMARY CORNER DESCRIPTION Cor. Secs. 7 & 18 (West) only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records, Vol. 19 Pages 7877-78)

Set post for corner from which:

- A Chinquapin, 8" dia. bears N.52°W., 137 lks. dist.
- A Fir, 18" dia. bears S.48°W., 26 lks. dist.
- A Fir, 18" dia. bears N.64°E., 30 lks. dist.
- A Yew, 14" dia. bears S.42°E., 52 lks. dist.

Resurvey of North 2 miles of the West Bdy., T31S R5W by Wm. P. Wright under Contract #281 dated May 16, 1878 (DCSO Records, Vol. 19 Page 13667)

Near the top of mountain. Still not finding fir post or evidence of post. Reestablish the same by setting a post 5" x 5" dia., by 4 ft. long, 20" in ground for corner to secs. 7, 18, 12 and 13, from which

- A Chinquapin 4" dia., bears S.80°W., 10 lks.
- A Red Fir 30" dia., bears N.60°E., 40 lks.
- A Laurel 12" dia., bears S.65°E., 46 lks.
- A Maple 2" dia., bears S.16°W., 28 lks.

B.L.M. Resurvey - John M. Jelley, Lynn M Roseberry, Floyd A Brooks, under Group #s 320 & 614, surveyed, June 1966 through May 1968. (DCSO records Vol. 35, Pg.14377)

Found, Original bearing tree -

- A Fir, 58" dia. bears N.60°E., 40 lks. dist. with scribe marks S7 BT visible on opened blaze.

Set - An iron post, 28" long, 2½" dia. 22" in ground with brass cap marked:

T	31	S
R	6	W
S	12	S
S	13	S
	18	
	1966	

from which new bearing trees

- A Fir, 15" dia. bears S.25°E., 87½ lks. dist. marked:
T31S R5W S18 BT
- A Fir, 20" dia. bears S.53½°W., 164 lks. dist. marked:
T31S R6W S13 BT
- A Fir, 19" dia. bears N.7°W., 75 lks. dist. marked:
T31S R6W S12 BT

NOTE - Not at the sec. corner - see 1998 BLM resurvey Vol. 53 Pgs.20480-1 for sec. corner.


continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 7 & 18 (West) only

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

BLM dependent resurvey by Daniel E. Weller, Cadastral Surveyor, under Group #1884, surveyed July/Sept 1998. (DCSO records Vol. 53 Page(s) 20480-1)

 Intersect the E. bdy. of sec. 12, T. 31 S., R. 6 W., true point for the cor. of secs. 7 and 18 only.
 Set a stainless steel post, 28" long, 2½" dia., 21" in the ground, and brass cap mkd. T 31 S



from which

A fir, 9" dia. bears N.83½°E., 68 lks. mkd. T31S R5W S7 BT

A fir, 11" dia., bears S.38°W., 9 lks., mkd. X BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

The cor. of secs. 7, 12, 13, and 18, established by Wright, bears N.87°43'54"W., 1.093 chs., monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, in a collar of stone, with brass cap mkd. T31S R6W R5W S12 S7 S13 S18 1966, from which the remains of an original bearing tree:

A fir, 61" dia., bears N.60°E., 40 lks., with scribe marks

T31S BT visible on opened blaze.

and the remains of bearing trees mkd. by Jelley, Roseberry, and Brooks

A fir, 28" dia., bears S.28¼°E., 87½ lks., with a healed blaze. (Record, S.25°E.)

A burnt fir stump, 29" dia., bears S.54½°W., 164 lks., with a healed blaze. (Record, S.53½°W.)

A fir, 28" dia., bears N.7°W., 75 lks., with a healed blaze.

Remark the brass cap to read AM 72.15 FT TO COR 1998 and an arrow pointing to the corner.