

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 7 (West) only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Daniel E. Weller, Cadastral Surveyor, under Group #1884, surveyed July/Sept 1998. (DCSO records Vol. 53 Page(s) 20473)

Point for the ¼ sec. cor. of sec. 7 only, at midpoint latitudinally bet. the cor. of secs. 7, 12, 13 and 18, and the cor. of secs. 1, 6, 7 and 12 established by Wright, and on the true W. bdy. of sec. 7, T31S R5W.

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, and brass cap mkd.

T 31 S
R 6 W R 5 W
| ¼
| S 7
1998

from which

A fir, 15" dia., bears N.38°E., 33½ lks., mkd. ¼ S7 BT.

A fir, 9" dia., bears S.49½°E., 37 lks., mkd. ¼ S7 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

The corner is located 55 lks. east of dirt skid road, 18 lks. wide, bears N. and S.