

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records, Vol. 19 Page 7884)

Set 1/4 Section post from which:
A Fir, 7" dia. bears N.73°30'W., 24 lks. dist.
A Fir, 6" dia. bears S.35°E., 14 lks. dist.

Oregon State Bd. of Forestry; Arnold G. Gibson, Wit: D.Ray & R.Olson. April 7, 1964 - C.S. File 51/264.

Found - Orig. post, now missing, from which:
7" Fir, bears N.73½°W., 24 lks.; now 18" down rotted log, portion of cast of scribe remaining.
6" Fir, bears S.35°E., 14 lks.; now missing, burnt out. Original (109 yr.old) line blazes on Township line west.
67 year old line blazes on same line west and north. Very burnt, old cruiser marks on large Firs in the SE, SW & NE.
"X" on down Cedar 34 ft. West.
N. & S. ridge 12 lks. E; in place. Ravine S.2.28 ch. W. in place.
Set - 1½" x 36" Gal. I.P. with 3" Brass Cap marked: "ORE ST BD of FORESTRY ¼ S31 S6 1964 RS 359" 30" in ground and from which a:
10" Fir, bears S.6½°W., 18.5 ft. scribed "¼ S6 BT"
38" Fir, bears N.18½°W., 50.4 ft. scribed ¼ S31 BT RS 359"
4"x4"x72" white painted cedar post 1.5 ft. NW of corner pipe.
Ore.St.Forestry Dept. metal location poster on 24" Fir bears S.12°W., 14.0 ft.

Lloyd "David" Smith - For: State of Oregon, Dept. of Forestry - June 1998 - M 129-8

Found - Oregon St. Board of Forestry 1½"x36" galvanized IP w/3" bronze cap, North & South ridge East 12 lks. 1964
10" Fir, S.6½°W., 18.5', now 14"x6" high, rotten stump, face missing. 1964
38" Fir, N.18½°W., 50.4', now 40"x1' high stump, face missing. 1964
4"x4"x72" White painted Cedar post, NW 1.5'.
24" Fir, S.12°W., 14.0', yellow metal location poster only, now 27"x3' high stump in place, yellow metal location poster. 1964
(Cont. next page)

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 31, only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Re-witnessed -
13" Fir, N.29°W., 18.2' to aluminum nail in BT face, scribed "¼ S31 BT", BT tag.
6" Fir, N.22°E., 20.2' to aluminum nail in BT face scribed X at DBH & BT at base of tree. BT
Orange carsonite marker CBM-250 labled witness post, N.61°E., 1.70' to base.
Orange carsonite marker CBM-250 labled witness post, N.89°W., 4.35', to base.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2883, surveyed March 2018/April 2018 - (DCSO records Vol. 59 Page(s) 23927-8)

The ¼ sec. cor. of sec. 31 only, on the S. bdy. of the Tp., perpetuated by Gibson, in 1964; subsequently perpetuated by Smith, in 1998; from orig. evidence no longer in existence; monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with a brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Gibson
A sawed, decayed fir stump, 14" dia., bears S.5½° W., 18.2 ft., no marks visible.
A sawed fir stump, 40" dia., bears N.19°W., 51.5 ft., with lower portion of the healed blaze.
and the bearing trees mkd. by Smith
A fir, 8" dia., bears N.19¼°E., 20.0 ft., with a healed double blaze.
A fir, 16" dia., bears N.32½°W., 18.6 ft., with a healed blaze.
Remove the marks S 6 from the brass cap and add the marks 2018 BLM.
The cedar post placed by Gibson, 4" square, painted white, is alongside the corner.
From the corner, W., at:
35 ft., dist. creek, 3 ft. wide, course S.25°E.
150 ft., dist. shallow ravine, 4 ft. wide, drains S.10°E.