

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 140140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Lloyd "David" Smith - For: State of Oregon, Dept. of Forestry
- June 1998 - M 129-8

Set - Oregon St. Dept of Forestry 1½" x 36" aluminum pipe
with 3¾" aluminum cap & magnetic insert, 34" in
ground.
8" Tan Oak, S.75°E., 20.0' to aluminum nail in BT face
scribed "C¼ S31 BT". BT tag.
8" Fir, S.43°W., 17.3' to aluminum nail in BT face
scribed "C¼ S31 BT". BT tag.
10" Fir, S.80°W., 16.6', to aluminum nail in BT face
scribed "C¼ S31 BT". BT tag.
21" W.Fir, N.21°W., 7.5' to aluminum nail in BT face
scribed "C¼ S31 BT". BT tag.
4"x4"x72" White painted Cedar post, N.75°E., 6.1'.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2883, surveyed March 2018/April
2018 - (DCSO records Vol. 59 Page(s) 23927-28)

The center ¼ sec. cor. of sec. 31, established by Smith, in
1998; and is accepted as the cor.; monumented with an
aluminum post, 2" dia., firmly set, projecting 1" above
ground, with a brass cap (properly) mkd.
from which the bearing trees mkd. by Smith
A chinquapin, 9" dia., bears S.67½°E., 20.2 ft., with
scribe marks C¼ S31 BT visible on partially healed
blaze.
A fir, 10" dia., bears S.39¾°W., 17.3 ft., with a healed
blaze.
A fir, 14" dia., bears S.75¾°W., 16.8 ft., with a healed
blaze.
A fir, 26" dia., bears N.23¼°W., 8.1 ft., with a healed
blaze.
From the corner, S.86°38'26"W., at:
85 ft. dist., creek, 3 ft. wide, course S.20°E.
325 ft. dist., same creek, 4 ft. wide, course S.30°E.