

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7932-33)

Set a Cedar post, 3" square, 3 ft. long, 18" in ground for the ¼ sec. cor., marked ¼ S on the N. face, from which
A Fir 20" dia., bears N.70°E., 28 lks. dist. marked ¼ S BT.
A Fir 24" dia., bears S.35°W., 9 lks. dist., marked ¼ S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: D. Bagger, R. Schulson, H.B. Baughn - Aug. 1963 - C.S. File 51/264

Original Cedar stake missing, from which a:
20" Fir bears N.70°E., 28 lks., now 42" stump.
24" Fir bears S.35°W., 9 lks., now 36" uproot stump, scribes ¼S visible in bark.
Set 1½" x 36" galv. iron pipe with 3" cap mkd: "Ore.St.Bd. of Forestry ¼ S30 S31 1963 RS 359", 30" in ground and from which:
23" Hemlock bears S.26°W., 25.8 ft. scribed ¼ S31 BT.
23" Cedar bears N.24°E., 28.1 ft. scribed ¼ S30 BT RS 359.
Set 4" x 4" x 72" white painted Cedar post 3.0 ft. N. of corner pipe.
Ore. St. Forestry Dept. metal location poster on Cedar BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and Joe Brady - May 1966 - C.S. File 54/25-1

Found - 23" Cedar now 24", N.24°E., 28.1 ft. scribed ¼ S30 BT. Top half of tree broken out.
23" Hemlock, now stump, S.26°W., 25.8 ft. "BT" scribe visible.
Oregon State Board of Forestry Brass cap at cor.
New BTs -15" Hemlock S.21°W., 31.3 ft. scribed ¼ S31 CS BT.
14" Hemlock N.29°W., 61.9 ft. scribed ¼ S30 CS BT.
Logging road bears West, 160.0 ft. Put location tag on road.

Lloyd D. Smith, L.S. #1101 - For: State of Oregon, Dept. of Forestry - May 1995 - M 122-17

Found - OSBF P/C, 1963
20" Fir, (1882) N.70°E., 28 lks. (Now 42" rotted stump, in place)
24" Fir, (1882) S.35°W., 9 lks. (Now 36" rotted uproot stump)
(Cont. Next Page)

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

23" Hemlock, (1963) S26°W., 25.8' (Now 23"x3' high rotted stump in place, scribes BT visible)
23" Cedar, (1963) N.24°E., 28.1' (Now 34"x2' high stump in place, scribe "0" visible)
1963 WPCP (4"x4"x72" white painted cedar post) North 3.0' (in place)
15" Hemlock, (1966) S.21°W., 31.3' (Now 22" in place, face closed)
14" Hemlock, (1966) N.29°W., 61.9' (Now 24"x1' high stump in place, face exposed w/axe work visible)
Logging road west 160.0' w/location tag (in place).
New B0s- WP (Orange carsonite marker CBM-250R Labeled witness post) N.51°W., 2.80' to base.
WP (Orange carsonite marker CBM-250R Labeled witness post) S.88°E., 3.30' to base.

Lloyd "David" Smith - For: State of Oregon, Dept. of Forestry - June 1998 - M 129-8

Condition report only
Found - Oregon St. Board of Forestry 1½"x36" gal. IP w/3" bronze cap. 1963
1882 20" Fir, N.70°E., 28 lks., now 42" rotten stump.
24" Fir, S.35°W., 9 lks., now 36" rotten uprooted , stump. 1882
23" Hemlock, S.26°W., 25.8', now 23"x3' high, rotten stump in place, scribes visible. 1963
1963 23" Cedar N.24°E., 28.1', now 34"x2' high stump.
15" Hemlock, S.21°W., 31.3', now 23", face closed. 1966
14" Hemlock, N.29°W., 61.9', now 24"x1' high stump, face exposed with axe work visible.
4"x4"x72" White painted Cedar post.
Logging road West, 160.0, yellow metal location poster.
Orange carsonite marker CBM-250 labeled witness post, N.51°W., 2.80' to base.
Orange carsonite marker CBM-250 labeled witness post, S.88°E., 3.30' to base.

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 8/2017 - C.S. File 65/95-60

Found - 3" State Forestry brass cap (properly mkd)
42" rotten fir stump N.70°E., 18.5 ft.
36" uprooted stump S.35°W., 5.9 ft. cont.

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

23" hemlock stump (3' high) S.26°W., 25.8 ft. vis scribes.
34" cedar stump N.24°E., 28.1 ft.
24" hemlock stump N.29°W., 61.9 vis. scribes.
26" hemlock S.21°W., 31.3 ft. good scar.
2 carsonite post per record.
New - 15" cedar N.13°E., 5.6 ft. scribed ¼ S30 BT.
24" fir S.37°E., 14.4 ft. scribed ¼ S31 BT.
Note - Corner is approx 160' east of Canyon Creek Road crossing tag on road.
Compass decl. 15½°E.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2883, surveyed March 2018/April 2018 - (DCSO records Vol. 59 Page(s) 23927-8)

The ¼ sec. cor. of secs. 30 and 31, perpetuated by Gibson, in 1963; subsequently perpetuated by Powell, in 1966; further perpetuated by Smith, in 1995; and further perpetuated by Quimby, in 2017; monumented with an iron post, 2½" dia., firmly set, projecting 7" above ground, with a brass cap (properly) mkd.
from which the remains of the original bearing trees
A sawed, decayed fir stump, 42" dia., bears N.70°E., 18.5 ft., no marks visible.
A roothole bears S.35°W., 5.9 ft., downhill of which is a down decayed fir, 35" dia., no marks visible.
and the remains of the bearing trees mkd. by Gibson
A sawed, decayed cedar stump, 27" dia., bears N.23¾°E., 29.0 ft., with a healed blaze.
A sawed, decayed hemlock stump, 18" dia., bears S.26¼°W., 26.3 ft., with illegible scribe marks visible on open blaze.
and the remains of the bearing trees mkd. by Powell
A hemlock, 26" dia., bears S.22¼°W., 31.0 ft., with a healed blaze.
A sawed, decayed hemlock stump, 26" dia., bears N.31¾°W., 57.6 ft., no marks visible.
and the bearing trees mkd. by Quimby
A cedar, 15" dia., bears N.9°E., 5.5 ft., with scribe marks ¼ S30 BT visible on open blaze.
A fir, 23" dia., bears S.42¾°E., 14.4 ft., with scribe marks ¼ S31 BT visible on open blaze.
The cedar post placed by Gibson, 4" square, painted white, is alongside the cor.
Corner is located W., 155 ft. of a graveled road, 14 ft. wide, bears N.20°E. and S.10°W.