

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Corner for Sections 7 & 18.

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records, Vol. 19 Page 7885 and (Vol.33 Pg. 13667, duplicate)

-----  
Set post 4 x 4 ins. dia. 4 ft. long 18" in ground, on hill side facing E. Very steep for  $\frac{1}{4}$  sec. cor. from which:  
A Fir, 30" dia. bears N.38°E., 15 lks. dist.  
A Fir, 20" dia. bears N.84°W., 60 lks. dist.

B.L.M. Resurvey - John M. Jelley, Lynn M Roseberry, Floyd A Brooks, June 1966 through May 1968. (DCSO records Vol. 35, Pg.14376-77)

-----  
Set at proportionate distance, an iron post, 28" long, 2 $\frac{1}{2}$ " dia. 24" in ground with brass cap marked:

T 31 S R 5 W

$\frac{1}{4}$  S 7  
4 S 18

1966

from which

A Fir, 13" dia. bears N.34°W., 169 lks. dist. mkd:  $\frac{1}{4}$  S7 BT  
A Chinquapin, 15" dia. bears S.21°W., 202 lks. mkd:  
 $\frac{1}{4}$  S18 BT.

Fd. & used on BLM dependent resurvey by Daniel E. Weller, Cadastral Surveyor, under Group #1884, surveyed July/Sept 1998. (DCSO records Vol. 53 Page(s) 20479-80)